

7700DA-DS3

DS3 Distribution Amplifier



The 7700DA-DS3 Distribution Amplifier provides automatic coaxial cable equalization, reclocking and signal distribution of DS3 (44.736 Mb/s) signals. The 7700DA-DS3 accepts a B3ZS-encoded Alternate Mark Inversion (AMI) input signal and provides four reclocked outputs.

The 7700DA-DS3 occupies one card slot and can be housed in either a 1RU frame that will hold up to 3 modules or a 3RU frame that will hold up to 15 modules.

Features

- Supports DS3 (44.736 Mb/s)
- Accepts B3ZS AMI input signals
- Adaptive cable Equalization for up to 300m of high quality 75 ohm cable
- Signal reclocking and optional jitter attenuator
- Output wave shaping for DS3 standards compliance
- Hi/Low output amplitude setting for Long/Short cable lengths
- Loss of signal (LOS) detection/indication
- Outputs 1s pattern generation upon loss of input signal
- Output drive level control for enhanced distance
- Transformer coupled inputs/outputs
- Input/output transient protection

Specifications

Inputs:

Standards:	DS3 (44.736Mb/s B3ZS)
Connector:	Isolated BNC per IEC 169-8
Impedance:	75 Ω (nominal)
Equalization:	Automatic to 300m with Belden 8281 cable
Return Loss:	> 15dB to 50MHz

Outputs:

Connectors:	BNC per IEC 169-8
Impedance:	75 Ω (nominal)
DC Offset:	0V nominal
Return Loss:	> 15dB to 50MHz
WB Jitter:	< 0.1UI

Electrical:

Voltage:	+12 VDC
Power:	6 Watts

Ordering Information:

7700DA-DS3:	DS3 Distribution Amplifier
--------------------	----------------------------

Ordering Options

Rear plate must be specified at time of order
Eg: **Model +3RU**

Rear Plate Suffix:

+3RU:	3RU rear plate for use with 7700FR-C Multiframe
--------------	---

+1RU: 1RU rear plate for use with 7701FR Multiframe

+SA: Standalone Enclosure Rear Plate

Enclosures:

7700FR-C: 3RU Multiframe which holds 15 modules

7701FR: 1RU Multiframe which holds 3 modules

S7701FR: Standalone Enclosure

7700DA-DS3 Block Diagram

