




RTS + OMNEO

= the ultimate IP solution for intercom . . .






RTS OMI ADAM matrix card

This card fits into the standard slots of the RTS ADAM or ADAM-M frames and provides a gateway to the world of OMNEO IP-compatible networking. The card consists of the traditional ADAM front and back card components and enhances ADAM systems with the following features:

- The OMI card is available in configurations up to 64 bidirectional ports in increments of 16 ports on a single card.
- The OMI card can be expanded from the base configuration of 16 ports through software upgrades.
- In addition to the standard RJ45 Ethernet connection, fiber connectivity is also supported with the addition of optional single mode or multimode modules.
- A fully configured single compact ADAM-M frame can support up to 256 OMNEO ports, providing a highly compact single frame solution for many system installs.
- The ADAM frame supports an astounding 512 OMNEO ports, making it ideal for larger systems without the need for frame-to-frame linking.

RTS OKI keypanel interface card



This card fits into select RTS user stations and provides native OMNEO IP connectivity for RJ45 Ethernet connections into the OMNEO network with optional single or multimode fiber modules. The card provides a two-port switch onboard as a pass-thru connection to allow daisy chaining of keypanels if required. It plugs into the existing header in the keypanel and comes with all parts needed to complete the upgrade.

The OKI card is available for the RTS KP-32, KP 32 CLD or KP 12 CLD keypanel.


Optional accessories for OMI and OKI cards



Fiber connections are fully supported when the OMI or OKI cards are used in conjunction with the single mode or multimode fiber modules shown. These modules are easily plugged into the slot on the back of the card and support full fiber connectivity.

Mixed ADAM system with analog, RVON and OMNEO connectivity

RTS+OMNEO ADAM intercom systems now have the ultimate in design and deployment flexibility.



RTS+OMNEO media networking supports a PURE IP network infrastructure. Deploying a new RTS intercom solution has never been easier: an entire ADAM system can now be connected via OMNEO. Systems can be trunked together and user stations can be deployed all over standard Ethernet hardware. With the inherently high audio quality and low latency of the OMNEO connection, OMNEO links can be employed anywhere there is sufficient network bandwidth.

Adding OMNEO-connected user stations is easy with the new OMI and OKI card sets. Most existing ADAM intercom systems will support OMNEO connectivity by upgrading the ADAM system firmware and using the new IP-edit configuration application. Current RTS analog user stations and trunks will seamlessly integrate with the new OMNEO connected keypanels. The system will perform as it always has, with the exception that now you can expand your network with standard IP network hardware.

RTS + OMNEO

... with pure IP connectivity, ultra-low latency and full HD audio

OMNEO is a media networking architecture for professional applications. Using standard IP Ethernets, media products that integrate OMNEO can be assembled into networks of 2 to 10,000 cooperating devices that exchange studio-quality synchronized multichannel audio and share common control systems.

OMNEO's media transport technology is Audinate's Dante, a high-performance, standards-based, routable IP media transport system. OMNEO's system control technology is Open Control Architecture, or OCA. OCA is an open public standard for the control and monitoring of professional media networks.

Interoperability and Standards


OMNEO media networking has been designed from the ground up to be based on open public standards which are freely available to all without restriction. OMNEO leads the way toward interoperability by utilizing standards from the IEEE and IETF for media transport and will comply with emerging standards, such as AVB.

The control and configuration component OCA has been openly published as a proposed standard and is on track to be standardized by the AES under the project designation X-210. OMNEO is able to utilize standard Ethernet and IT hardware or infrastructure, but will also be able to take advantage of AVB-enabled bridges as these become available.

The new RTS ADAM OMNEO interface cards transform the ADAM intercom system into a flexible, IP-based, AVB-compatible intercom network. OMNEO media networking architecture **goes beyond** traditional AVB solutions by incorporating both industry standard OCA control and IP audio. OMNEO will interoperate with AVB and Dante devices, ensuring future interconnectivity with a growing number of devices. ADAM OMNEO products open the door to deploy ADAM intercom systems over any standard IP-based network. Most importantly, with OMNEO users are not "locked in" to other vendors' proprietary backbone infrastructure. This makes RTS the leading IP open network solution for professional production intercoms.

With RTS+OMNEO, such essential tasks as deploying intercom user stations, linking via trunking and interfacing to third party devices has now become easier and more flexible. The addition of ADAM OMNEO cards to any compatible ADAM system means even existing installations can be networked over standard IP hardware with high quality, ultra-low-latency audio.


The product range consists of the ADAM OMNEO card for the ADAM and ADAM-M intercom frames and a user station interface card for select RTS keypad models. Both these cards fully update the connectivity of these RTS intercom products to be fully IP compatible.



Specification Table

	OMI ADAM Matrix Card	OMI Keypanel Interface Card
Supporting Products	ADAM, ADAM-M	KP-32, KP 32 CLD, KP 12 CLD
Connections		(2) RJ45 Ethernet Connections (1) LC Type SFP Fiber Connector
Audio I/O Levels	N/A. See note below*	Input/Output (maximum level): +20 dBu Input/Output (nominal level): +8 dBu
Frequency Response (Input)		within ± 1 dB from 20 Hz – 20 kHz
THD+N at 1 kHz	better than 0.01% @ 8 dB	—
Network Delay		<20 ms typical
Storage Temperature	-40°F to 158°F (-40°C to 70°C)	KP 12 CLD/KP 32 CLD: -40°F to 158°F (-40°C to 70°C) KP-32 : -40°F to 140°F (-40°C to 60°C)
Operating Temperature	32°F to 122°F (0°C to 50°C)	KP 12 CLD/KP 32 CLD: 5°F to 122°F (-15°C to 50°C) KP-32: 14°F to 105.8°F (-10°C to 41°C)
Power Consumption	14.9 W @ 5 V (Front and Back combined)	KP 12 CLD/KP 32 CLD without Fiber: 5 watts KP 12 CLD/KP 32 CLD with Fiber: 5.75 watts KP-32 without Fiber: 5.5 watts KP-32 with Fiber: 6.25 watts
Weight	Front Card: 0.65 lb (0.29 kg) Back Card: 0.30 lb (0.14 kg)	4.15 oz (card only)
Card Dimensions (W x D x H)	Front Card: 0.8" x 12.7" x 6.8" (21.04 cm x 322.40 cm x 173.11 cm) Back Card: 0.8" x 6.8" x 6.8" (20.0 cm x 172.56 cm x 172.26 cm)	4.5" x 3.0" x 1.1" (29.03 cm x 19.35 cm x 7.10 cm)

*OMI card is a digital board with build-in audio mixer for 64 inputs. The audio I/O levels are specific to analog sources such as AIO-16 or keypad.



Americas
 Bosch Security Systems, Inc.
 12000 Portland Ave South
 Burnsville, MN 55337 | United States
 USA—Phone: +1-877-863-4169 | Fax: +1-800-955-6831
 Canada—Phone: +1-866-505-5551 | Fax: +1-866-336-8467
 Latin America—Phone: +55 19 2103-2860 | Fax: +55 19 2103-2860