

The new Blackmagic Mini Converter range are the worlds most advanced converters because they include the latest 6G-SDI technology, plus automatically detect the input video format and instantly change between virtually all SD, HD and Ultra HD video standards! Simply plug in and Mini Converters will convert between your equipment all automatically!

You get advanced features such as redundant SDI inputs, re-clocked loop outputs and full analog and AES/EBU audio inputs and outputs so you can convert between formats as well as embed or de-embed audio all on the one converter! Choose from a range of 13 models depending on the conversion you need!



Easy To Use Features

Broadcast, post production and professional AV environments are built using SDI equipment and cabling. It's essential when converting to and from SDI that you maintain the highest possible video and audio quality. Mini Converters are compact, affordable and easy-to-use. Settings can be changed quickly using built-in mini switches, and with a diagram showing pin settings printed on the back you never need to refer to a manual! Mini Converters use standard broadcast video and audio connections, so you get the convenience and cost savings of using your own cables!

Choose from a range of the world's greatest converters!



Ultra HD and 6G-SDI Technology

Make the move to Ultra HD, the broadcast standard of the future, easy! Be prepared now by installing equipment that is fully compatible with all your SD and HD-SDI infrastructure, but will also switch over to Ultra HD via 6G-SDI when you need to run Ultra HD! This means you're ready for the future and can build your system with full Ultra HD compatibility! Ultra HD features an incredible 4 times the resolution of regular 1080 HD video for a massive 3840 x 2160 frame size! Ultra HD is amazing! The advanced 6G-SDI design also means the new Blackmagic Mini Converters models perform better when used in SD and HD formats than simple HD only converters!



Standard Audio Connections

Mini Converters support embedded SDI and HDMI audio and several models let you



Powerful Performance

Unlike other converters that can be confusing to operate and sometimes



Optical Fiber Conversion

Mini Converter is available in a 6G-SDI to optical fiber model. You get bi-directional

separately embed or de-embed analog or digital audio. Mini Converters support 24 bit analog and AES/EBU audio and use standard 1/4" audio jacks so you don't need custom cables!

identify, Mini Converters combine powerful performance with a simple, compact design! Built-in connections are easy to access and all use standard cables that you're already likely to own!

6G-SDI to optical fiber conversion, with each direction independent of each other. Optical fiber cables span distances up to 28 miles without any deterioration to the signal.

SDI to HDMI 4K

Highest Quality Processing

With the highest quality video processing, Mini Converters are ideal for all broadcast, post production and professional AV applications. Multiple internal power supplies ensure incredibly low noise levels when moving between analog and digital video formats. Specific models include up/down/cross conversion that lets you move easily between PAL and NTSC SD video standards and the high number of HD formats in up to 3840 x 2160 Ultra HD resolutions.

Easy Settings Control

Changing Mini Converter's built-in mini switch settings is as easy as using a pen! This is great when you need to change settings quickly as there are no complicated menus to navigate! You can also control settings using the included Converter Utility software.

Connect a Mini Converter to any Mac OS X or Windows based laptop or desktop computer! All models can be updated via USB 2.0 by simply downloading software upgrades directly from the Blackmagic Design website.



Next 🕨

Mini Converters Family



Mini Converter SDI to HDMI 4K Convert SDI in SD, HD and UltraHD to HDMI 4K with analog and AES audio.

\$295

Buy Now



Mini Converter HDMI to SDI 4K Convert SD, HD and UltraHD HDMI with HDMI/analog or AES audio to SDI.

\$295


Buv Now







	\$295		\$295
	Buy Now		Buy Now
	sector and the sector	<u>م</u>	
Mini Converter SDI to Audio SD/HD/3G-SDI audio de embedder to 8 ch AES/EBU or 4 ch analog audio.	Mini Converter Optica Independent bi-directional e optical fiber and optical fiber	5G-SDI to	Mini Converter SDI Multiplex 4K Convert between Single Link 6G-SDI, Dual Link 3G-SDI and Quad Link HD-SDI 4K.
\$495		\$495	\$495
Buy Now		Buy Now	Buy Now
	Mill Convertien ()	<u>a</u>	
Mini Converter Audio to SDI SD/HD/3G-SDI audio embedder from 8 ch AES/EBU or 4 ch analog audio.	Mini Converter Optica Independent bi-directional S fiber and optical fiber to SE	SDI to optical	Mini Converter SDI Distribution 4K Distribute to 8 x SDI outputs in all formats including SDI, HD-SDI, 3G-SDI and 6G- SDI.
\$495		\$295	\$295
Buy Now		Buy Now	Buy Now
	- Without and the second secon		
Mini Converter Sync Generator Sync generator for black burst and HD tri- sync reference signals.	Mini Converter UpDo Up, down and cross convert NTSC/PAL standards conve	ter, includes full	Mini Converter Quad SDI to HDMI 4K Connect 6G-SDI, Dual Link 3G-SDI or
\$295		\$495	Quad Link HD-SDI to HDMI 4K \$495
\$29 <i>3</i>		Puy Nov	ψ+25
Buy Now		Buy Now	Buy Now

All items on this website are copyright Blackmagic Design Pty. Ltd. 2014, all rights reserved. All trademarks are property of their respective owners MSRP excludes sales taxes/duties and shipping costs.





MSRP excludes sales taxes/duties and shipping costs.



Mini Converter SDI to HDMI 4K

SDI Video Input

SDI Video Output (4K HDMI output only)

1 x SD, HD or 6G-SDI.

Technical Specifications

Description


Connections

Mini Converter SDI to HDMI 4K includes everything you need to convert from SD, HD, 3G and 6G-SDI video sources to HDMI in SD, HD and Ultra HD video formats. You can also de-embed SDI audio to HDMI, AES/EBU or balanced analog audio out. Imagine using big screen Ultra HD TV's and projectors for broadcast monitoring! The built in down converter even allows Ultra HD monitoring on HD televisions!

Price \$295

Updates and Configuration Via USB 2.0 high speed. (480 Mb/s)

Reclocking Yes



input is lost. Multi Rate Support

Automatically switches over if main SDI

SDI Redundant Input

Standards

SD Format Support 525/29.97 NTSC, 525/23.98 NTSC, 625/25 PAL

HD Format Support

720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60,1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60

2K Format Support

2048x1080PsF23.98, 2048x1080p23.98, 2048x1080PsF24, 2048x1080p24, 2048x1080PsF25, 2048x1080p25

4K Format Support

SDI Compliance

SMPTE 292M, SMPTE 259M, SMPTE 296M, SMPTE 372M, SMPTE 424M and SMPTE 425M.

SDI Video Rates

SDI video connections are switchable between standard definition, high definition and 6G-SDI.

SDI Video Sampling 4:2:2 and 4:4:4

SDI Audio Sampling Television standard sample rate of 48 kHz

and 24 bit.

SDI Color Precision 4:2:2 and 4:4:4

SDI Auto Switching

Automatically detects SD, HD or 6G-SDI.


HDMI Format Support

625/25 PAL, 525/29.97 NTSC, 525/23.98 NTSC, 720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 2048x1080p23.98, 2048x1080p24, 2048x1080p25, 3840x2160p23.98, 3840x2160p24, 3840x2160p25, 3840x2160p29.97, 3840x2160p30, 4096x2160p24

HDMI Color Space YUV and RGB

	3840x2160p23.98, 3840x2160p24, 3840x2160p25, 3840x2160p29.97, 3840x2160p30, 4096x2160p24	4:2:2 and 4:4:4 SDI Color Space YUV and RGB	HDMI Color Precision 4:2:2 and 4:4:4
Software	Software Control Mac OS X^{TM} and Windows TM software upgrade via USB.	Internal Software Upgrade Via included updater application.	
Settings Control	Mini Switches or USB software.		
Power Requirements	Power Supply +12V universal power supply included with international socket adapters for all countries. Cable tie point.	Power Consumption 5.2 Watts	Operational Voltage Range 12 - 30 V DC
Physical Specifications	4.49 in	т 0.90 in 	
Environmental Specifications	Operating Temperature 0° to 40° C (32° to 104° F)	Storage Temperature -20° to 45° C (-4° to 113° F)	Relative Humidity 0% to 90% non-condensing
What's Included	Mini Converter SDI to HDMI 4K Software CD 12V universal power supply with international s	ocket adapters	
Warranty	3 Year Limited Manufacturer's Warranty.		
			Next
Mini Converte	ers Family		
Mini Converter S Convert SDI in SD, I	SDI to HDMI 4K HD and UltraHD to HDMI 4K with analog and A	ES Convert SD, HD and Ultr	AII to SDI 4K aHD HDMI with HDMI/analog or AES audio
audio.	\$295	to SDI.	\$295

Blackmagic Design: Mini Converters Tech Specs



All items on this website are copyright Blackmagic Design Pty. Ltd. 2014, all rights reserved. All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.