


**SWIT Electronics USA, LLC.**

SEARCH

Go

[Field LCD Monitor](#)
[Rack-Mount Monitor](#)
[Studio Monitor](#)
[Power Station Box](#)
[V-Mount Battery](#)
[Gold-Mount Battery](#)
[NP-1 Style Battery](#)
[Charger / Adaptor](#)
[Converter/Distributo](#)
[Fiber Camera System](#)
[Wireless Transmission System](#)
[LED Light](#)
[Battery for Sony](#)
[Battery for Panasonic](#)
[Battery for Canon](#)
[Battery for JVC](#)
[Accessories](#)
[Gra-Vue Products](#)
[AViPAS Products](#)
[B-Stock & Clearance](#)
[Dealers/ Rentals](#)
[Sales Reps](#)
[Shipping & Returns](#)
[Material Safety Data Sheets](#)
[FAQ](#)
[Home](#) > [Converter/Distributor](#) > S-4600 SDI to HDMI Converter

## S-4600 SDI to HDMI Converter



Item# S-4600

**\$235.00**
**Availability:** Usually ships the next business day

[Add to cart](#)

### Product Description



The S-4600 is a portable 3GSDI to HDMI converter. It converts the 3GSDI with its embedded audio to HDMI output, and supports 3GSDI loop through output and SDI embedded audio via 3.5mm earphone output.

The S-4600 is heavy duty housing design, protecting the BNC connectors well, and supplies various screw threads at the bottom, for convenient installing, and future accessories (battery mount, etc.)

### Key Features:

- Portable 3G/HD/SD-SDI to HDMI Converter
- 1x 3GSDI input, 1x HDMI output and 1x 3GSDI loop through output
- SDI audio output via 3.5mm socket
- Embed SDI audio to HDMI output
- Power/input/output status indicator
- Heavy duty aluminium housing
- Bottom screw threads for installing

### Specifications:

Input	
BNC x 1	3G/HD/SD-SDI input
Output	
BNC x 1	3G/HD/SD-SDI loop output
HDMI x 1	Converted HDMI output
3.5mm x 1	SDI audio output
Video Format	
SDI	SMPTE-425M 1080p (60 / 59.94 / 50)
	SMPTE-274M 1080i (60 / 59.94 / 50)
	1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211 1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M 720p (60 / 59.94 / 50)
	SMPTE-125M 480i (59.94)
	ITU-R BT.656 576i (50)
HDMI	1080p (60/ 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
	1080i (60 / 59.94 / 50)
	720p (60 / 59.94 / 50)
	480i / 576i
Audio	48KHz Sync
General	
Power	≤3W
Working Voltage	DC 6-18V
Working Environment	Temperature: 0°C-+70°C, Humidity:10%-90%
Dimensions	98x84x29 mm
Net weight	200g

### Standard Package

S-4600 standard package includes:

- 1x AC-DC power adaptor (A-PA03)
- 1x Install plate (A-IP00)

**Warranty Period:** Two years conditional.

[View S-4600 User Manual](#)

