



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AViPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Converter/Distributor](#) > S-4601 HDMI to SDI Converter

S-4601 HDMI to SDI Converter



Item# S-4601

\$245.00

Availability: Usually ships the next business day

[Add to cart](#)

Product Description



S-4601 is a HDMI to 3G/HD/SD-SDI converter. It supports HDMI audio embedded into SDI output; analog audio (3.5mm socket) input, embedded into SDI output.

S-4601 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing, and future accessories (battery mount, etc)

Key Features:

- Portable HDMI to 3G/HD/SD-SDI Converter
- 1 HDMI input, 2 SDI output,
- 1 analog audio (3.5mm) input
- Embed HDMI audio to SDI output
- Embed analog audio (3.5mm) to SDI output
- HDCP content not supported
- Power/input/output status indicator
- Heavy duty housing
- Bottom screw threads for installing

Specifications:

Input		
HDMI x 1	HDMI Input	
3.5mm x 1	Analog audio input	
Output		
BNC x 2	Converted 3G/HD/SD-SDI output	
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
HDMI	1080p (60/ 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
	1080i (60 / 59.94 / 50)	
	720p (60 / 59.94 / 50)	
	480i / 576i	
Audio	48KHz Sync	
General		
Power	≤3W	
Working Voltage	DC 6-18V	
Working Environment	Temperature: 0°C-+70°C, Humidity:10%-90%	
Dimensions	98x84x29 mm	
Net weight	210g	

Standard Package

- S-4601 standard package includes:
- 1x AC-DC power adaptor (A-PA03)
 - 1x Install plate (A-IP00)

Warranty Period: Two years conditional.

[View S-4601 User Manual](#)

