



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributor](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AVIPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Converter/Distributor](#) > S-4606 OPTICAL to SDI Converter

S-4606 OPTICAL to SDI Converter



Item# S-4606

\$480.00

Availability: Usually ships the next business day

[Add to cart](#)

Product Description

The S-4606 is a portable Optical fiber to 3G/HD/SD-SDI converter. The single-mode fiber ensures max 20km reliable transmission, and support hot swap of optical module. The S-4606 is heavy duty housing design, protecting the BNC connectors well, and supplied various screw threads in the bottom, for convenient installing.

Key Features:

- Portable Optical Fiber to 3G/HD/SD-SDI Converter
- 1 Optical input, 2 SDI output
- Single-mode Optical fiber, LC connector
- Max 20km reliable transmission
- Support hot swap of optical module
- Power/SDI input status indicator
- Heavy duty aluminium housing
- Bottom screw threads for installing

Specifications:

Input		
LC x 1		Optical fiber Input
Output		
BNC x 2		Converted 3G/HD/SD-SDI output
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
Optical Fiber		SMPTE 297-2006 1260-1580nm wavelength
General		
Power		≤3W
Working Voltage		DC 6-18V
Working Environment		Temperature: 0°C-+70°C, Humidity:10%-90%
Dimensions		98x84x29 mm
Net weight		220g


Input and Output

- S-4606 offers:
- 1x LC Optical Fiber input
 - 2x 3G/HD/SD-SDI loop output



Encoder and Decoder

The S-4606 works as decoder to convert Optical fiber back to SDI, and you can use SWIT S-4605 (SDI to Optical fiber encoder) together, to transmit SDI via fiber up to 20km reliable distance.



Status Indicators

S-4606 provides 2 LED indicators, to check if the power is connected, and if the output SDI is recognized.



Power Supply

The mini converter is powered by pole-tap DC socket. The package includes an AC-DC power adaptor, and you can also connect DC cable from 6-18V batteries.



Heavy Duty Housing

The S-4606 mini converter adopts unibody aluminium alloy housing, strong for field using and protects the BNC connectors effectively.

Installation

S-4606 provides the bottom 1/4-inch screw threads for fixing on cameras, and an installing plate A-IP00 is supplied in the package, for fixing on wall and binding the BNC cables and optical fibers.

Standard Package

- S-4606 standard package includes:
- 1x AC-DC power adaptor (A-PA03)
 - 1x Install plate (A-IP00)



Standard Package

- S-4606 standard package includes:
- 1x AC-DC power adaptor (A-PA03)
 - 1x Install plate (A-IP00)

Warranty Period: Two years conditional.

[View S-4606 User Manual](#)

