



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AVIPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Converter/Distributor](#) > S-4611 SDI to DVI Converter

S-4611 SDI to DVI Converter



Item# S-4611

\$249.00

Availability: Usually ships the next business day

[Add to cart](#)

Product Description



S-4611 is a mini converter for SDI to DVI conversion, (DVI-D, 18+1 connector), which can be widely used to display up to 3Gb/s broadcast SDI video on DVI monitor, televisions, LED board or projectors.

Key Features:

- Portable 3G/HD/SD-SDI to DVI Converter
- 1 SDI input, 1 DVI output, and 1 SDI loop
- SDI audio output via 3.5mm socket
- Power/input/output status indicator
- Pole-tap 6-18V DC power input
- Heavy duty aluminium housing
- Bottom screw threads for installing

Specifications:

Input		
BNC x 1		3G/HD/SD-SDI input
Output		
BNC x 1		3G/HD/SD-SDI loop output
DVI-D x 1		Converted DVI output
3.5mm x 1		SDI audio output
Video Format		
SDI	SMPTE-425M	1080p (60 / 59.94 / 50)
	SMPTE-274M	1080i (60 / 59.94 / 50)
		1080p (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)
	SMPTE-296M	720p (60 / 59.94 / 50)
	SMPTE-125M	480i (59.94)
ITU-R	BT.656	576i (50)
DVI		1080p (60/ 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)
		1080i (60 / 59.94 / 50)
		720p (60 / 59.94 / 50)
		480i / 576i
Audio		
General		
Power		≤3W
Working Voltage		DC 6-18V
Working Environment		Temperature: 0°C-+70°C, Humidity:10%-90%
Dimensions		98x84x29 mm
Net weight		207g

Input and Output

S-4611 offers:

- 1x 3G/HD/SD-SDI input
 - 1x 3G/HD/SD-SDI loop output (Reclocked)
 - 1x DVI-D output
 - 1x 3.5mm audio output
- (The SDI to DVI supports the same format conversion only.)



Embedded Audio output

The SDI embedded audio ch-1 & ch-2 can be converted to analog audio and output via 3.5mm headphone socket, supports 48kHz sample rate.



Status Indicators

S-4611 provides 3 LED indicators, to check if the power is connected, and if the input/output signal is delivered.



Power Supply

The mini converter is powered by pole-tap DC socket. The package includes an AC-DC power adaptor, and you can also connect DC cable from 6-18V batteries.



Heavy duty Housing

The S-4611 mini converter adopts unibody aluminium alloy housing, strong for field using and protects the BNC connectors effectively.

Installation

S-4611 provides the bottom 1/4-inch screw threads for fixing on cameras, and an installing plate A-IP00 is supplied in the package, for fixing on wall and binding the BNC/DVI cables.



Standard Package:

- S-4611 standard package includes:
- 1x AC-DC power adaptor (A-PA03)
- 1x Install plate (A-IP00)

Warranty Period: Two years conditional.

[View S-4611 User Manual](#)

