



SWIT Electronics USA, LLC.

SEARCH

Go

[Field LCD Monitor](#)[Rack-Mount Monitor](#)[Studio Monitor](#)[Power Station Box](#)[V-Mount Battery](#)[Gold-Mount Battery](#)[NP-1 Style Battery](#)[Charger / Adaptor](#)[Converter/Distributo](#)[Fiber Camera System](#)[Wireless Transmission System](#)[LED Light](#)[Battery for Sony](#)[Battery for Panasonic](#)[Battery for Canon](#)[Battery for JVC](#)[Accessories](#)[Gra-Vue Products](#)[AViPAS Products](#)[B-Stock & Clearance](#)[Dealers/ Rentals](#)[Sales Reps](#)[Shipping & Returns](#)[Material Safety Data Sheets](#)[FAQ](#)[Home](#) > [Accessories](#) > S-7100S V-mount to 4-pin XLR Cable

S-7100S V-mount to 4-pin XLR Cable



Item# S-7100S

\$29.00**Availability:** Usually ships the next business day[Add to cart](#)

Product Description



The S-7100S directly connects to pins of V-mount batteries and provides 14.4V DC output through a 4-pin XLR connector. (Battery sold separately.)

Key Features:

- 14.4V DC output
- 4-pin XLR connector
- V-mount battery applicable

Specifications:

Output voltage	DC 14.4V
Applicable battery	V-mount battery
Cable length	Approx 6.6ft/ 2m

Warranty Period: One year conditional.