



SWIT Electronics USA, LLC.

SEARCH

Go

[Field LCD Monitor](#)[Rack-Mount Monitor](#)[Studio Monitor](#)[Power Station Box](#)[V-Mount Battery](#)[Gold-Mount Battery](#)[NP-1 Style Battery](#)[Charger / Adaptor](#)[Converter/Distributo](#)[Fiber Camera System](#)[Wireless Transmission System](#)[LED Light](#)[Battery for Sony](#)[Battery for Panasonic](#)[Battery for Canon](#)[Battery for JVC](#)[Accessories](#)[Gra-Vue Products](#)[AViPAS Products](#)[B-Stock & Clearance](#)[Dealers/ Rentals](#)[Sales Reps](#)[Shipping & Returns](#)[Material Safety Data Sheets](#)[FAQ](#)[Home](#) > [Accessories](#) > S-7102 4-pin XLR Female to Male, S-3802A/S Output Cable

S-7102 4-pin XLR Female to Male, S-3802A/S Output Cable



Item# S-7102

\$27.00**Availability:** Usually ships the next business day[Add to cart](#)

Product Description



The S-7102 is an adaptor cable for S-3802A/S charger, provides 14.4V DC output through a 4-pin XLR connector.

Key Features:

- 14.4V DC output
- 4-pin XLR connector
- S-3802A/S output cable

Specifications:

Output voltage	DC 14.4V
Cable length	Approx 10ft/3m

Warranty Period: One year conditional.