



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AVIPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Gold-Mount Battery](#) > S-8082A 95Wh Gold Mount Battery

S-8082A 95Wh Gold Mount Battery



Item# S-8082A

\$270.00

Availability: Usually ships the next business day

[Add to cart](#)

Product Description



S-8082A is a lightweight 95Wh Gold-mount battery, with a D-tap socket for camera light or other equipments. It has a 4-level LED indicator to give the user a view of remaining power before mounting to camera.

The Li-ion contents of S-8082A comply with the IATA safe air transportation regulations. It is not restricted from being taken onto an airplane or shipped as air cargo.

Key Features:

- Li-ion battery, no memory effect
- 14.4V, 95Wh large capacity
- D-tap output socket
- 4-level LED power indicator
- Metal Gold-mount plate
- Wireless receiver mount
- Safe air transportation

Specifications:

Voltage	14.4V
Capacity	95Wh/6.6Ah
Max Output Power	50W
Max Output Current	3.5A
Mount Type	Gold-mount
Operation temperature	0- 40°c
Net Weight	Approx 0.8kg
Dimension	134x88x54mm

95Wh / 6.6Ah High Capacity

Consists of 12pcs 18650 battery cells, and reaches 95Wh / 6.6Ah high capacity. Can run approx 3 hours for normal 30W ENG cameras.



AntonBauer Gold Mount Connection

S-8082A is compatible with AntonBauer Gold mount type power system and we adopt the high quality connection bolts that ensure the reliable mounting.



Build-in D-tap DC Output Socket

A D-tap DC output socket is equipped on the top side of S-8082A battery, for DC14.4V (Nominate) connection, such as on-camera lights, monitors, wireless transmitter, etc. The Max Power from D-tap is 50W, 3.5A.



4-level LED Power Indicator

On the side of the battery, there are 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



Warranty Period: Two years conditional.

Related Items:

- [S-3802A: 2-channel Gold mount battery Charger](#)
- [D-3004A 4-channel Gold mount battery Charger](#)
- [SC-304A 2-channel Simultaneous Gold-Mount Charger](#)
- [S-3010A: Portable charger for Gold mount battery](#)
- [S-3010B: Portable charger for battery with D-tap](#)

[View Batteries Compatibility Chart](#)

[View Chargers Compatibility Chart](#)

[View S-8082A User Manual](#)

