



SEARCH

Go

[Field LCD Monitor](#)[Home](#) > [V-Mount Battery](#) > S-8082S 95Wh V-Mount Battery[Rack-Mount Monitor](#)

S-8082S 95Wh V-Mount Battery

[Studio Monitor](#)[Power Station Box](#)[V-Mount Battery](#)[Gold-Mount Battery](#)[NP-1 Style Battery](#)[Charger / Adaptor](#)[Converter/Distributo](#)[Fiber Camera System](#)[Wireless Transmission System](#)[LED Light](#)[Battery for Sony](#)[Battery for Panasonic](#)[Battery for Canon](#)[Battery for JVC](#)[Accessories](#)[Gra-Vue Products](#)[AViPAS Products](#)[B-Stock & Clearance](#)[Dealers/ Rentals](#)[Sales Reps](#)[Shipping & Returns](#)[Material Safety Data Sheets](#)[FAQ](#)

Item# S-8082S

\$270.00**Availability:** Usually ships the next business day[Add to cart](#)

Product Description



S-8082S is a lightweight 95Wh V-mount battery, with a D-tap socket for camera light or other equipments. It has a 4-level LED indicator to give the user a view of remaining power before mounting to camera. The Li-ion contents of S-8082S comply with the IATA safe air transportation regulations. It is not restricted from carry-on nor from shipping as air cargo.

Key Features:

- Li-ion battery, no memory effect
- 14.4V, 95Wh large capacity
- D-tap output socket
- 4-level LED power indicator
- Metal V-mount plate
- Wireless receiver mount
- Safe air transportation

Specifications:

Voltage	14.4V
Capacity	95Wh
Max Output Power	50W
Max Output Current	3.5A
Over Current Protection	5A
Mount Type	V-mount
Operation temperature	0- 40°c
Net Weight	Approx 0.76kg
Dimension	134x88x52mm

Warranty Period: Two years conditional.

Related Items:

Chargers:

- [S-3802S: 2-channel V-mount battery Charger](#)
- [D-3004S 4-channel Digital V-mount battery Charger](#)
- [SC-304S 2-channel Simultaneous V-mount Charger](#)
- [S-3010S: Portable charger for V-mount battery](#)
- [S-3010B: Portable charger for battery with D-tap](#)

[View Batteries Compatibility Chart](#)[View Chargers Compatibility Chart](#)[View S-8082S User Manual](#)