



SEARCH

[Field LCD Monitor](#)

[Rack-Mount Monitor](#)

[Studio Monitor](#)

[Power Station Box](#)

[V-Mount Battery](#)

[Gold-Mount Battery](#)

[NP-1 Style Battery](#)

[Charger / Adaptor](#)

[Converter/Distributo](#)

[Fiber Camera System](#)

[Wireless Transmission System](#)

[LED Light](#)

[Battery for Sony](#)

[Battery for Panasonic](#)

[Battery for Canon](#)

[Battery for JVC](#)

[Accessories](#)

[Gra-Vue Products](#)

[AViPAS Products](#)

[B-Stock & Clearance](#)

[Dealers/ Rentals](#)

[Sales Reps](#)

[Shipping & Returns](#)

[Material Safety Data Sheets](#)

[FAQ](#)

[Home](#) > [Gold-Mount Battery](#) > S-8083A 130Wh Gold Mount Battery

S-8083A 130Wh Gold Mount Battery



Item# S-8083A

\$325.00

Availability: Usually ships in 1-2 weeks

Product Description

S-8083A is the AntonBauer gold mount rechargeable Li-ion battery pack for professional video cameras. It's compact design, smaller in size.

Key Features

- Li-ion, 14.4V, 130Wh capacity
- D-tap output socket
- 100W/8A power output
- 4-level LED power indicator
- Gold mount connection
- Multiple circuit protections

Specifications:

Normal Voltage	14.4V
Capacity	130Wh/9.2Ah
Max output power	100W
Max output current	8A
Mount type	Gold mount
Operation temperature	0- 40°C
Net Weight	Approx. 0.8kg
Dimension	134x88x54mm

130Wh / 9.2Ah Capacity

Consists of 12pcs 18650 battery cells, and reaches 130Wh/9.2Ah high capacity. Run approx 4 hours for normal 30W ENG cameras.



AntonBauer Gold Mount Connection

S-8083A is compatible with AntonBauer Gold mount type power system and we adopt the high quality connection bolts that ensure the reliable mounting.



Build-in D-tap DC Output Socket

A D-tap DC output socket is equipped on the top side of S-8083A battery, for DC14.4V (Nominate) connection, such as on-camera lights, monitors, wireless transmitter, etc. The Max Power from D-tap is 100W, 8A.



4-level LED Power Indicator

On the side of the battery, there're 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



Warranty Period:Two years conditional.

User Manual:

[View S-8083A User Manual](#)

Related Items:

[S-3802A: 2-channel Gold Mount battery Charger](#)

[D-3004A 4-channel Digital Gold Mount battery Charger](#)

