



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AViPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [V-Mount Battery](#) > S-8083S 130Wh V-mount Battery

S-8083S 130Wh V-mount Battery



Item# S-8083S

\$325.00

Availability: Usually ships in 1-2 weeks

[Add to cart](#)

Product Description



S-8083S is the V-mount rechargeable Li-ion battery pack for professional video cameras. It's compact design, smaller in size.

Key Features:

- Li-ion, 14.4V, 130Wh capacity
- D-tap output socket
- 100W/8A power output
- 4-level LED power indicator
- V-mount connection
- Multiple circuit protections

Specifications:

Normal Voltage	14.4V
Capacity	130Wh/9.2Ah
Max output power	100W
Max output current	8A
Mount type	V-mount
Operation temperature	0- 40°C
Net Weight	Approx. 0.8kg
Dimension	134x88x52mm

130Wh / 9.2Ah Capacity

Consists of 12pcs 18650 battery cells, and reaches 130Wh/9.2Ah high capacity. Run approx 4 hours for normal 30W ENG cameras.



Reliable V-mount Connection

S-8083S is the standard SONY V-mount connection and we adopt the high quality metal V-wedge that ensures the reliable mounting.



Build-in D-tap DC Output Socket

A D-tap DC output socket is equipped on the top side of S-8083S battery, for DC14.4V (Nominate) connection, such as on-camera lights, monitors, wireless transmitter, etc. The Max Power from D-tap is 100W, 8A.



4-level LED Power Indicator

On the side of the battery, there're 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



Warranty Period:Two years conditional.

User Manual:

[View S-8083S User Manual](#)

Related Items:

- [S-3802S: 2-channel V-mount battery Charger](#)
- [D-3004S 4-channel Digital V-mount battery Charger](#)

