



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AViPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Gold-Mount Battery](#) > S-8110A 126Wh Gold Mount Battery

S-8110A 126Wh Gold Mount Battery



Item# S-8110A

\$350.00

Availability: Usually ships the next business day

[Add to cart](#)

Product Description



S-8110A is a lightweight 126Wh Gold-mount battery, it has a 4-level LED indicator to give the user a view of remaining power before mounting to camera. The built-in intelligent circuit has multiple protections of abnormal current, voltage and temperature.

[IATA restrictions for traveling with Larger Lithium ion batteries](#)

Note: The restrictions maybe are different between different airlines.

Key Features:

- 14.4V, 126Wh large capacity
- 4-level LED power indicator
- Metal Gold-mount plate
- D-tap output socket
- Multiple circuit protections

Specifications:

Voltage	14.4V
Capacity	126Wh/8.8Ah
Max Output Power	100W
Max Output Current	8A
Over Current Protection	10A
Mount Type	Gold-mount
Operation temperature	0- 40°c
Net Weight	Approx 0.9kg
Dimension	165x90x53mm

126Wh / 8.8Ah High Capacity

Consists of 24pcs 18650 battery cells, and reaches 126Wh / 8.8Ah high capacity. Can run approx 4 hours for normal 30W ENG cameras.



AntonBauer Gold Mount Connection

S-8110A is compatible with AntonBauer Gold mount type power system and we adopt the high quality connection bolts that ensure the reliable mounting.



Build-in D-tap DC Output Socket

A D-tap DC output socket is equipped on the top side of S-8110A battery, for DC14.4V (Nominate) connection, such as on-camera lights, monitors, wireless transmitter, etc. The Max Power from D-tap is 100W, 8A.



4-level LED Power Indicator

On the side of the battery, there are 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



Warranty Period: Two year conditional.

Related Items:

- [S-3802A: 2-channel Gold mount battery Charger](#)
- [D-3004A 4-channel Gold mount battery Charger](#)
- [SC-304A 2-channel Simultaneous Gold-Mount Charger](#)
- [S-3010A: Portable charger for Gold mount battery](#)
- [S-3010B: Portable charger for battery with D-tap](#)

[View Batteries Compatibility Chart](#)

[View Chargers Compatibility Chart](#)

[View S-8110A User Manual](#)

