



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributo](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AViPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Gold-Mount Battery](#) > S-8192A 92Wh+92Wh Split-Style Battery

S-8192A 92Wh+92Wh Split-Style Battery



Item# S-8192A

\$460.00

Availability: Usually ships the next business day

Product Description



Large Capacity Battery, Complied with IATA

The IATA DGR regulations restricted the air transportation of over 100Wh Li-ion battery packs:

Battery Capacity	Carry-on Baggage	Air Cargo Shipping
Under 100Wh	OK	OK
100Wh-160Wh	Only 2pcs allowed	Not allowed
Over 160Wh	Not allowed	Not allowed

Since the large capacity batteries are quite necessary, SWIT provides the solution of Dividable Battery to comply with IATA regulations. S-8192A can be divided into 2 parts, and each part contains 92Wh capacity, not restricted by air transportation. And when using S-8192A, just assemble the 2 parts, you can get a Li-ion battery pack of 184Wh large capacity.

[IATA restrictions for traveling with Larger Lithium ion batteries](#)

Note: The restrictions maybe are different between different airlines.

Key Features:

- Divide into 2 parts of 92Wh capacity each (Patent)
- Not restricted by IATA air transportation regulations
- Li-ion, 14.4V, 92+92Wh capacity
- D-tap output socket
- 4-level LED power indicator
- Gold mount type connection
- Multiple circuit protections

Specifications:

Normal Voltage	14.4V
Capacity	92Wh+92Wh / 6400mAh+6400mAh
Max output power	100W
Max output current	8A
Mount type	Gold-mount
Operation temperature	0- 40°C
Net Weight	Approx. 1.2kg
Dimension	168x101x65mm

184Wh / 12.8Ah High Capacity

When assembled, the S-8192A consists of 20pcs 18650 battery cells, and reaches 184Wh / 12.8Ah high capacity. S-8192A can run approx 6 hours for normal 30W ENG cameras, and has no problem to fly with.



AntonBauer Gold Mount Connection

S-8192A is compatible with AntonBauer Gold mount type power system and we adopt the high quality connection bolts that ensure the reliable mounting.



Build-in D-tap DC Output Socket

A D-tap DC output socket is equipped on the top side of S-8192A battery, for DC14.4V (Nominate) connection, such as on-camera lights, monitors, wireless transmitter, etc. The Max Power from D-tap is 100W, 8A.



4-level LED Power Indicator

On the side of the battery, there are 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



Warranty Period: Two years conditional.

Related Items:

- [S-3802A: 2-channel Gold-mount battery Charger](#)
- [D-3004A 4-channel Digital Gold-mount battery Charger](#)
- [SC-304A 2-channel Simultaneous Gold-Mount Charger](#)
- [S-3010A: Portable charger for Gold-mount battery](#)
- [S-3010B: Portable charger for battery with D-tap](#)

[View Batteries Compatibility Chart](#)

[View Chargers Compatibility Chart](#)

[View S-8192A User Manual](#)

