



SEARCH

- [Field LCD Monitor](#)
- [Rack-Mount Monitor](#)
- [Studio Monitor](#)
- [Power Station Box](#)
- [V-Mount Battery](#)
- [Gold-Mount Battery](#)
- [NP-1 Style Battery](#)
- [Charger / Adaptor](#)
- [Converter/Distributor](#)
- [Fiber Camera System](#)
- [Wireless Transmission System](#)
- [LED Light](#)
- [Battery for Sony](#)
- [Battery for Panasonic](#)
- [Battery for Canon](#)
- [Battery for JVC](#)
- [Accessories](#)
- [Gra-Vue Products](#)
- [AViPAS Products](#)
- [B-Stock & Clearance](#)
- [Dealers/ Rentals](#)
- [Sales Reps](#)
- [Shipping & Returns](#)
- [Material Safety Data Sheets](#)
- [FAQ](#)

[Home](#) > [Battery for Canon](#) > S-8845 DV Battery with DC Output for Canon BP-945/970G

## S-8845 DV Battery with DC Output for Canon BP-945/970G



Item# S-8845

**\$98.00**

**Availability:** Usually ships the next business day

[Add to cart](#)

### Product Description

- Li-ion battery pack of 7.2V nominal voltage
- Comparable to Canon BP series DV battery
- 47Wh / 6.6Ah capacity
- 4-level LED power indicator
- 7.2V/5.5mm Pole-tap DC output
- Multiple circuit protections

### Canon BP series Replacement battery

S-8845 is the replacement battery for Canon BP series BP-945/BP-970G, compatible with Canon XF100/105 and EOS C300



### 47Wh / 6.6Ah Capacity

With 7.2V nominal voltage, the S-8845 has 47Wh / 6.6Ah capacity, and can run approx. 7 hours on XF105 when LCD monitor is on, and approx. 4.5 hours on Canon EOS C300.



### Build-in Pole-tap DC Output Socket

A 5.5/2.1mm pole-tap DC output socket is equipped on the side of S-8845 battery, for DC 7.2V (Nominate) connection. You can connect on-camera LED light, monitor or wireless transmitter on the pole-tap socket, and get power simultaneously with camera. The Max power from the pole-tap is 30W, 4A. The Pole-tap socket can also be used as charging input, by SWIT portable charger S-3010D.



### 4-level LED Power Indicator

The S-8845 battery has the 4-level LED power indicators to check the battery remaining capacity. You can get a quick view of capacity before using.



### Easy Charging

The S-8845 can be charged on SWIT Dual channel charger S-3602C. It takes about 4 hours and 30 minutes to charge from empty to 100%. And you can also use SWIT S-3010D Portable Pole-tap Charger for S-8845. It will take 7 hours to fully charge.



### Specifications:

Nominal Voltage	7.2V	
Capacity	47Wh,6.6Ah	
Max output power	Total	45W,6A
	Pins	30W,4A
	Pole-tap	30W,4A
Applicable camera	Canon XF100/105, EOS C300	
Net weight	Approx 300g	
Dimensions	71 3/8" x 38 3/8" x 70mm	

**Warranty Period:** One year conditional.

### Related Items:

[SWIT S-3602C charger/adaptor for Canon](#)

[View S-8845 User Manual](#)

