

SONY

HDC-P50 Multi-Purpose Camera



4K

Sony proudly introduces to its lineup a point-of-view (POV)-style 4K camera, the HDC-P50, to increase your creativity, boost performance, and add flexibility while maintaining interchangeability with existing models.

The HDC-P50 is a highly compact POV-style multi-purpose camera based on Sony's sophisticated core technologies and equipped with the latest three 2/3-inch 4K CMOSs with Global Shutter.

The HDC-P50 offers shooting flexibility from almost anywhere and delivers high-quality 4K pictures as a standalone camera or system camera integrating seamlessly with the HDC-4300 and HDC-3500 Series. Precise adjustment of camera parameters can also be achieved with the remote control panel (RCP) and master setup unit (MSU) developed for Sony's HDC Series system cameras.

The compact and lightweight HDC-P50 is an ideal POV camera for a wide range of uses including unmanned studio robotics cameras, wireless applications with a Steadicam, and deployment at stadiums, gymnasiums, and other sporting events.

Features

Compact Design with High Picture Quality

Packed in a highly slim and compact body of only about 112 mm (4 1/2 inches) in width and weighing around 2.7 kg (5 lb 15 oz) excluding a lens, the HDC-P50 is equipped with three superb 2/3-inch 4K CMOSs with Global Shutter and Sony-developed digital processing LSI, achieving high picture quality equivalent to that of reputable HDC Series cameras.

The HDC-P50 is ideal for use in space-limited areas such as camera crane jibs, helicopter camera mounts, and stereoscopic 3D camera rigs.



Dual Optical Servo Filters

The HDC-P50 is equipped with Neutral Density (ND) and Color Correction (CC) optical servo filter units, which can be remotely controlled according to lighting condition changes from a remote control panel (RCP) or a master setup unit (MSU).

Master Setup Unit and Remote Control Panel

You can use the MSU-1000/MSU-1500 Master Setup Unit (MSU) and RCP-1000 Series Remote Control Panel (RCP) developed to adjust HDC-P50 camera parameters.



MSU-1000
Master Setup Unit



MSU-1500
Master Setup Unit



RCP-1000
Remote Control Panel



RCP-1001
Remote Control Panel



RCP-1500
Remote Control Panel


Multi-Format Operation

This camera supports a wide range of capturing formats such as 1080/59.94i, 1080/50i, 1080/59.94p^{*1}, 1080/50p^{*1}, 720/59.94p, 720/50p, 1080/23.98PsF^{*2}, 24PsF^{*2}, 25PsF^{*2}, and 29.97PsF^{*2}.

*1 Optional HZC-PRVP50 software is required.

*2 Optional HZC-PSFP50 software is required.

System Configuration (LAN connection)





Rear View



Dimensions

Unit: mm (inches)



Specifications

General	
Power requirements	TBD
Operating temperature	20°C to +45°C (.4°F to +113°F)
Storage temperature	20°C to +60°C (.4°F to +140°F)
Mass	2.7 kg (5 lb 15 oz)
Camera section	
Imager	3-chip 2/3-inch type 4K CMOS with global shutter
Effective resolution (H x V)	3840 x 2160
Signal format	1080/50i, 1080/59.94i, 720/50p, 720/59.94p (1080/23.98PsF, 1080/24PsF, 1080/25PsF, 1080/29.97PsF, 50/59.94p, 4K/50p, 4K/59.94p: option)
Spectrum system	F1.4 prism
Lens mount	Sony bayonet mount
Built-in filters	ND: 1: CLEAR, 2: 1/4ND, 3: 1/8ND, 4: 1/16ND, 5: 1/64ND CC: A: CROSS, B: 3200K, C: 4300K, D: 6300K
Sensitivity (at 2000 lx, 3200K, 89.9% reflectance)	F10 (at 1080/59.94p, 720/59.94p), F11 (at 1080/50p, 720/50p)
Signal-to-noise ratio	-62 dB or higher
Horizontal resolution	2,000 TV lines (at center)
Shutter speed	1/100, 1/125, 1/250, 1/500, 1/1000, 1/2000 sec (1080/59.94i) 1/60, 1/125, 1/250, 1/500, 1/1000, 1/2000 sec (1080/50i)
Inputs/Outputs	
Genlock input	BNC (x1) HD: SMPTE 274M, tri-level sync, 0.6 Vp-p, 75 Ω SD: Black burst (NTSC: 0.286 Vp-p, 75 Ω/PAL: 0.3 Vp-p, 75 Ω)
SDI 1 output	BNC (x1), 12G/3G/1.5G-SDI
SDI 2 output	BNC (x1), 12G/3G/1.5G-SDI
SDI 3 output	BNC (x1), 3G/1.5G-SDI
SDI 4 output	BNC (x1), 3G/1.5G-SDI
SDI MONI	BNC (x1), HD-SDI
EXT I/O	D-sub 15-pin (female) (x1)
Remote	8-pin (x1)
Lens	12-pin (x1)
LAN	RJ-45 (x1), 10BASE-T, 100BASE-TX
Supplied accessories	
Tally number plate (1set), CD-ROM (1)	

Design and specifications are subject to change without notice.

Optional Accessories

- RM-B170 (Remote Control Unit)
- MSU-1000/MSU-1500 (Master Setup Unit)
- RCP-1000/RCP-1500/RCP-1530 (Remote Control Unit)
- HZC-UHD50(Operating software for 4K/59.94p and 4K/50p)
- HZC-PRV50 (Operating software for 1080/59.94p and 1080/50p)
- HZC-PSF50 (Operating software for 1080/23.98PsF, 24PsF, 25PsF, and 29.97PsF)*

*PsF format will be available in 2019 September

Distributed by

©2018 Sony Imaging Products & Solutions Inc.
 Reproduction in whole or in part without written permission is prohibited.
 Features and specifications are subject to change without notice.
 The values for mass and dimension are approximate.
 "SONY" is a registered trademark of Sony Corporation.
 All other trademarks are the property of their respective owners.
 Please visit Sony's professional website or contact your Sony representative
 for specific models available in your region.