








General Information   **Key Features**   Specifications   Image gallery   ...

- **4K Modular Multiviewer system**
- **Hardware based (NO Pc, NO hard-drive)**
- **Easy to use scalable modular multiviewer system**
- **Up to 16 (3G/HD/SD-SDI) inputs in 1RU**
- **4 x 3G/HD SDI and 1 HDMI 4K output**
- **High quality image processing engine with low processing delay**
- **Quick control: Easy to use keyboard with user configurable direct keys and encoder**
- **Aspect Ratio Selection (4:3, 16:9)**
- **ATC & D-VITC Time code (SDI)**
- **Markers and safety areas**
- **No audio, Silence, No input and Black image on screen alarms**
- **16 Channel Audio Level Meters (embedded audio) (3G/HD/SD-SDI)**

- **Selectable format of Audio level meters (Vertical or Horizontal)**
- **NTP and Local Clocks and Timers**
- **16 characters UMD and video format information per input**
- **Tally and UMD, TSL 3.1 and 5.0 compatible**
- **Selectable Background, border, text color**
- **Free user friendly drag and drop control software and firmware update by USB**
- **SNMP Compatible system**
- **Redundant power supply**
- **Space-saving, fanless, energy-efficient and lightweight aluminium design**

### Professional broadcast adjustments

These multiviewer have all professional features and adjustments as UMD and Tally, Aspect Ratio Selection, Markers, 16 Channel Audio Level Meters, Alarms, Timecodes, Clocks & Timers,.. 4Craft integrate user configurable direct keys and encoder to easy navigate through the OSD menu. Any adjustment can be located in a direct key, to access functions just with a press, and keys LED lights can be turned off if required for dark environments.




#### Markers

Wide range of markers and security areas are available with line color and curtain transparency selection. A User Marker is available if any of standard markers fits your requirements.




#### Alarms

On screen video and audio alarms with selectable color and time selection. No Input, Black Image, No Audio, Silence.



#### Timecode and Source Format Information

On screen ATC Timecode information and Video Format Information



#### 16 Channel Audio Level Meter

Display up to 16 Channel Audio Level Meters with a wide range of options (All together, Separate in pairs-odds,.. Selectable Yellow and Red color level and two different sizes.




#### Tally and UMD

Red, Green and Yellow tally and 16 character UMD compatible with TSL 3.1 and TSL 5.0. Three tally modes available: Square, Border and UMD (all can be activated together)




#### Encoder & Dual Functionality Direct Keys

Encoder to easy navigate through the OSD menu, and direct keys with dual functionality (fixed/configurable). Activate [Fn] Mode to use F1 to F3 keys with your custom configuration and access your favourite adjustments just with a press. Keys LED lights can be turned off if required for dark environments.



#### Border & Text color selection

Selectable Border and Text color. Available colors: black, white, red, green, blue, cyan, magenta, yellow and 7 grey levels.



#### Clocks & timers

Display up to 2 clocks and 6 timers in your Layout. NTP and internal clocks and UP and Down Counters.



#### Soft4Boxes Pro Control Software

Soft4Boxes Pro is a software to control our Multiviewer Monitors and Video Processors. S4B PRO is an intuitive and user-friendly "drag & drop" control software.

\* Click here for more information!

### Follow us on Instagram to check #Craltechprojects



#### SUPPORT

PHONE +34 93 465 74 04  
FAX +34 93 465 02 31  
Language: ESP | ENG

#### NEWS


NEWS ON THE WEBSITE  
LAST NEWS ON TWITTER

#### INFO

ABOUT US  
DOWNLOAD OUR CATALOG  
2020

\* Specifications are subject to change without prior notifications

Follow us and stay connected at:







General Information

Key Features

Specifications

Image gallery

...

VIDEO INPUTS

- Up to 16 3G/HD/SD-SDI

3G-SDI

- SMPTE 424M-2006 level A
- Format: 1920x1080p (60, 59.94, 50)
- Cable lenght: 85m Belden 1694A
- BNC Connector

HD-SDI

- SMPTE 274M and SMPTE 296M
- Formats: 1080p (30, 29.97, 25, 24, 23.98, 30PsF, 29.97PsF, 25PsF, 24PsF, 23.98PsF) 1080i (60, 59.94, 50) 720p (60, 59.94, 50)
- Cable lenght: 100m Belden 1694A
- BNC Connector

SD-SDI

- SMPTE 125M/259M
- Formats: 480i (59.94) 576i (50)
- Cable lenght: 250m Belden 1694A
- BNC Connector

VIDEO OUTPUTS

- 1 x 4K HDMI UHD 25/30Hz Output and 1080i (50,60), 1080p (25, 30, 50)
- 4 X 3G/HD SDI Outputs: 1080i (50,60), 1080p (20,30,50,60)

GPIO CONNECTOR

- GND Contact closure

ETHERNET

- RJ-45 Connector

USB CONNECTOR

- Upgrade system

DIMENSIONS

- 426 x 43 x 212 mm (1RU)
- 2,5Kg

POWER REQUIREMENTS

- 12V DC (XLR Connector)
- Power consumption 24W

Follow us on Instagram to check #Craltechprojects



SUPPORT

PHONE +34 93 465 74 04  
FAX +34 93 465 02 31  
Language: ESP | ENG

NEWS


NEWS ON THE WEBSITE  
LAST NEWS ON TWITTER

INFO

ABOUT US  
DOWNLOAD OUR CATALOG  
2020

\* Specifications are subject  
to change without prior  
notifications

Follow us and stay  
connected at:





# 4K Modular Multiviewer


4craft  
K Multiview

4craft | one  
duo  
cuatro  
K Multiview

## Modular Multiviewer

3G SDI Inputs\* | HDMI Inputs\* | 4x 3G SDI Outputs | 4K Output | Cascade | PRO Tools

\* Up to 16 inputs (8 input boards)



4K OUTPUT  
MODULAR  
DESIGN

## Professional Modular 4K Multiviewer

The **4craft** is a compact (1U) 4K Multiviewer with superior quality image processing engine with low processing delay. The modular design allows to create custom solutions of up to 16 inputs (3G/HQ/SD SDI) and up to 4 outputs (3G/HQ/SD SDI), and display all inputs on-screen simultaneously in any size and position. Up to 6 layouts can be stored in the **4craft**.

**4craft** is an easy to use Multiviewer with Dual Functionality front keyboard and encoder for quick control and fast configuration of the equipment. With compact and Lightweight 1 RU Aluminium design, **4craft** is a fanless and energy-efficient Multiviewer that grant low temperature while working.



### Features:

- Hardware based (NO Pc, NO hard-drive)
- Up to 16 (3G/HQ/SD-SDI or HDMI) inputs in 1RU
- 4 x 3G/HQ SDI and 1 HDMI 4K output
- Low processing delay
- Quick control: Easy to use double function keyboard with user configurable direct keys and encoder
- Aspect Ratio Selection (4:3, 16:9)
- Markers and safety areas
- ATC & D-VITC Time code (SDI)
- No audio, Silence, No input and Black image on screen alarms
- Real time colour Waveform (Selectable RGB, R, G, B, YCbCr, Y, Cb, Cr) and Vectorscope per input
- 16 Channel Audio Level Meters (3G/HQ/SD-SDI embedded audio) (Vertical or Horizontal)
- NTP and Local Clocks and Timers
- 16 characters UMD and video format information
- Tally and UMD, TSL 3.1 and 5.0 compatible
- Redundant power supply
- Selectable Background, border and text colour
- Free user friendly control software (SNMP compatible) and firmware update by USB
- Space-saving, fanless, energy-efficient and lightweight aluminium design



# 4K Modular Multiviewer

4craft  
K Multiview

## 4craft cuatro K Multiview

**4craft cuatro** is an easy to use modular Multiviewer with **4 x 3G/HD SDI outputs and 4K HDMI output (25, 30, 50, 60Hz)** and 8 or 16 3G/HD/SD SDI or HDMI inputs. With superior quality image processing engine, the **4craft cuatro** is a hardware based Multiviewer with low processing delay.

**4craft cuatro** integrates our communications **B2B-Link system to cascade equipments without adding delay**, to increase the number of sources to be displayed in your system and an Ethernet connector to control the Multiviewer remotely using our user friendly drag and drop Remote Control Software (SNMP compatible).



3G SDI Inputs\* | HDMI Inputs\* | 4x3G SDI Outputs | 4K Output | Cascade | PRO Tools


\* Up to 16 inputs (8 input boards)

### Specifications

Video Inputs	8 or 16 (3/HD/SD SDI and/or HDMI)
3G-SDI	SMPTE 424M-2006 Level A, Format 1920x1080 (60, 59.94, 50) Cable length 85m Belden 1694A, BNC connector
HD-SDI	SMPTE 274M and SMPTE 296M, Formats 1080p (30, 29.97, 25, 24, 23.98, 30PsF, 29.97PsF, 25PsF, 24PsF, 23.98PsF) 1080i (60, 59.94, 50), 720p (60/59.94/50/30/29.97/25/24/23.98) Cable length 100m Belden 1694A, BNC connector
SD-SDI	SMPTE 125M/259M, Formats 480i (59.94), 576i (50) Cable length 250m Belden 1694A, BNC connector
Video Outputs	1 x 4K HDMI Output: 3840x2160 (25,30,50,60Hz), 1080i (50,60), 1080p (25, 30, 50) 4 x 3G/HD SDI Outputs: 1080i (50,60), 1080p (20,30,50,60)
Audio Output	Audio Jack phone
GPIO Connector	GND contact closure
Ethernet	RJ-45 Connector
USB Connector	Upgrades
Chassis	Aluminium. Textured Black powder Coat
Dimensions	426 x 43,6 x 212 mm (1RU)
Power supply	12V DC
Power consumption	TBD

### Ordering Information:


**4CRAFT-3G16:** 16x3G/HD/SD SDI inputs  
**4CRAFT-3G8:** 8x3G/HD/SD SDI inputs



**4CRAFT-HD16:** 16xHDMI inputs  
**4CRAFT-HD8:** 8xHDMI inputs



**4CRAFT-3G/HD8:** 8x3G/HD/SD SDI and 8xHDMI inputs





# 4K Modular Multiviewer

4craft  
K Multiview

## 4craft duo K Multiview

**4craft duo** is an easy to use modular Multiviewer with **2 x 3G/HD SDI outputs and 4K HDMI output (25, 30Hz)**, and 8 or 16 3G/HD/SD SDI or HDMI inputs. With superior quality image processing engine, the **4craft duo** is a hardware based Multiviewer with low processing delay.

**4craft duo** integrates Ethernet connector to control the Multiviewer remotely using our user friendly drag and drop Remote Control Software (SNMP compatible).



3G SDI Inputs\* | HDMI Inputs\* | 2x 3G SDI Outputs | 4K Output | Cascade | PRO Tools


\* Up to 16 inputs (8 input boards)

### Specifications

<b>Video Inputs</b>	8 or 16 (3/HD/SD SDI and/or HDMI)
<b>3G-SDI</b>	SMPTE 424M-2006 Level A, Format 1920x1080 (60, 59.94, 50) Cable length 85m Belden 1694A, BNC connector
<b>HD-SDI</b>	SMPTE 274M and SMPTE 296M, Formats 1080p (30, 29.97, 25, 24, 23.98, 30PsF, 29.97PsF, 25PsF, 24PsF, 23.98PsF) 1080i (60, 59.94, 50), 720p (60/59.94/50/30/29.97/25/24/23.98) Cable length 100m Belden 1694A, BNC connector
<b>SD-SDI</b>	SMPTE 125M/259M, Formats 480i (59.94), 576i (50) Cable length 250m Belden 1694A, BNC connector
<b>Video Outputs</b>	<b>1 x 4K HDMI Output: 3840x2160 (25,30Hz)</b> , 1080i (50,60), 1080p (25, 30, 50) <b>2 X 3G/HD SDI Outputs:</b> 1080i (50,60), 1080p (20,30,50,60)
<b>Audio Output</b>	Audio Jack phone
<b>GPIO Connector</b>	GND contact closure
<b>Ethernet</b>	RJ-45 Connector
<b>USB Connector</b>	Upgrades
<b>Chassis</b>	Aluminium. Textured Black powder Coat
<b>Dimensions</b>	426 x 43,6 x 212 mm (1RU)
<b>Power supply</b>	12V DC
<b>Power consumption</b>	TBD

### Ordering Information:


**4CRAFT-3G16D:** 16x3G/HD/SD SDI inputs  
**4CRAFT-3G8D:** 8x3G/HD/SD SDI inputs



**4CRAFT-HD16D:** 16xHDMI inputs  
**4CRAFT-HD8D:** 8xHDMI inputs



**4CRAFT-3G/HD8D:** 8x3G/HD/SD SDI and 8xHDMI inputs





# 4K Modular Multiviewer

4craft  
K Multiview

## 4craft one K Multiview

**4craft one** is an easy to use modular Multiviewer with **1 x 3G/HD SDI output and 4K HDMI output**, and 8 or 16 3G/HD/SD SDI or HDMI inputs. With superior quality image processing engine, **4craft duo** is a hardware based Multiviewer with low processing delay.

**4craft duo** integrates Ethernet connector to control the Multiviewer remotely using our user friendly drag and drop Remote Control Software (SNMP compatible).



3G SDI Inputs\* | HDMI Inputs\* | 1 3G SDI Outputs | 4K Output | Cascade | PRO Tools

\* Up to 16 inputs (8 input boards)

### Specifications

Video Inputs	8 or 16 (3/HD/SD SDI and/or HDMI)
3G-SDI	SMPTE 424M-2006 Level A, Format 1920x1080 (60, 59.94, 50) Cable length 85m Belden 1694A, BNC connector
HD-SDI	SMPTE 274M and SMPTE 296M, Formats 1080p (30, 29.97, 25, 24, 23.98, 30PsF, 29.97PsF, 25PsF, 24PsF, 23.98PsF) 1080i (60, 59.94, 50), 720p (60/59.94/50/30/29.97/25/24/23.98) Cable length 100m Belden 1694A, BNC connector
SD-SDI	SMPTE 125M/259M, Formats 480i (59.94), 576i (50) Cable length 250m Belden 1694A, BNC connector
Video Outputs	1 x 4K HDMI Output: 3840x2180 (25,30Hz), 1080i (50,60), 1080p (25, 30, 50) 1 X 3G/HD SDI Outputs: 1080i (50,60), 1080p (20,30,50,60)
Audio Output	Audio Jack phone
GPIO Connector	GND contact closure
Ethernet	RJ-45 Connector
USB Connector	Upgrades
Chassis	Aluminium. Textured Black powder Coat
Dimensions	426 x 43,6 x 212 mm (1RU)
Power supply	12V DC
Power consumption	TBD

### Ordering Information:

**4CRAFT-3G160:** 16x3G/HD/SD SDI inputs  
**4CRAFT-3G80:** 8x3G/HD/SD SDI inputs



**4CRAFT-HD160:** 16xHDMI inputs  
**4CRAFT-HD80:** 8xHDMI inputs



**4CRAFT-3G/HD80:** 8x3G/HD/SD SDI and 8xHDMI inputs



Specifications are subject to change without prior notifications

### Waveform and vectorscope per input

Locate them inside the window, inside or outside the image

### 2 Clocks and 6 Timers (NTP & Internal)


Locate them anywhere on the canvas

On Screen alarms  
NO AUDIO SILENCE  
NO INPUT BLACK

Markers & Safety Areas

Tally  
(TSL 5.0, TSL 3.1, GPIO)

Up to 16 Channels  
Audio Level Meters



Border & Background  
colour selection  
Easy group sources

Video format information

UMD 16 character

1 x 3G/HD SDI OUT and 1 x HD HDMI OUT (same layout in both outputs)

