

Products

- ▶ SMPTE Fiber Products
- ▶ 12G-SDI Products
- ▶ Cables
- ▶ Connectors
- ▶ Video Patchbays and Panels
- ▶ EO/OE Systems
- ▶ Cable Assemblies
- ▶ Cable Reels
- ▶ Tools

- Distributor Listing
- Catalog
- Tech Notes
- FAQ

▶ Video Fantails (3VS, 4VS, 5VS Series)



Product Image

Product Name

Video Fantails

Model Number

3VS, 4VS, 5VS Series

BNC (Multi)

High quality and reliable Canare assemblies are ideal for any inter connection including broad cast, professional A/V, and telecommunication.

- Custom assembly configurations can be special ordered at affordable cost and quick lead-time.
- True 75 Ohm BCP-A, -B Crimp Plugs.
- Super Flexible, Easy Payout & Wrap-up.
- 100% Test and Quality Controlled.
- Excellent Connector Pull Strength.
- Color Matching BNC Strain Relief Boots.
- Jacket Protection Sleeve at Fan Breakout.

Canare 75 Ohm VS component cable is available in a variety of pre-cut lengths terminated with our true 75 Ohm BNC crimp plugs. All assemblies are precisely timed with less than 2.2 nanoseconds between adjacent video channels. Canare VS fantails offer extra wide video bandwidth performance because cable and connectors are 75 Ohm impedance matched.

Custom assembly configurations can be special ordered using any of Canare's other V-Series models: **V-1.5C, V-3C, V-5C, V-3CFB, V-4CFB** and **V-5CFB** multichannel video snake series in a variety of metric lengths.

- <2.2 Nanoseconds Channel Delay.
- 75 Ohm Impedance.
- Please call for cable/connector configurations available.

MECHANICAL SPECIFICATIONS		MECHANICAL SPECIFICATIONS	
Model	Length (ft.) (m)	Model	Length (ft.) (m)
3VS01A-3C	3.28 (1.0)	3VS03A-5C	9.84 (3.0)
3VS02A-3C	6.56 (2.0)	3VS05A-5C	16.4 (5.0)
3VS03A-3C	9.84 (3.0)	3VS08A-5C	26.25 (8.0)
3VS05A-3C	16.4 (5.0)	3VS10A-5C	32.81 (10.0)
3VS08A-3C	26.25 (8.0)	3VS15A-5C	49.21 (15.0)
3VS10A-3C	32.81 (10.0)	3VS20A-5C	65.62 (20.0)
4VS01A-3C	3.28 (1.0)	4VS03A-5C	9.84 (3.0)
4VS02A-3C	6.56 (2.0)	4VS05A-5C	16.4 (5.0)
4VS03A-3C	9.84 (3.0)	4VS08A-5C	26.25 (8.0)
4VS05A-3C	16.4 (5.0)	4VS10A-5C	32.81 (10.0)
4VS08A-3C	26.25 (8.0)	4VS15A-5C	49.21 (15.0)
4VS10A-3C	32.81 (10.0)	5VS03A-5C	9.84 (3.0)
5VS01A-3C	3.28 (1.0)	5VS05A-5C	16.4 (5.0)
5VS02A-3C	6.56 (2.0)	5VS08A-5C	26.25 (8.0)
5VS03A-3C	9.84 (3.0)	5VS10A-5C	32.81 (10.0)
5VS05A-3C	16.4 (5.0)	5VS15A-5C	49.21 (15.0)
5VS08A-3C	26.25 (8.0)	5VS20A-5C	65.62 (20.0)
5VS10A-3C	32.81 (10.0)	5VS30A-5C	98.43 (30.0)
5VS15A-3C	49.21 (15.0)		
5VS20A-3C	65.62 (20.0)		
5VS30A-3C	98.43 (30.0)		