

## HDCU-3170

IP capable Triax Camera  
Control Unit



### Overview

#### **IP capable Triax Camera Control Unit**

The HDCU-3170 Triax Camera Control Unit is an ideal companion for the Sony HDC-3170 system camera. It also adds IP live production capabilities to our full range of broadcast and studio system cameras.

While it's intended primarily for triax operation, adding the HKCU-FB30 fibre option board makes the HDCU-3170 compatible with both triax and fibre systems – a benefit for production companies and OB trucks working in stadiums and venues with different transmission system.

By installing the optional 4K/HDR Processor Board HKCU-UHD30, the HDCU-3170 can output 4K signals when connected with an HDC-Series System Camera. In addition, adding the optional 12G-SDI Interface Kit HKCU-SDI30 allows transfer of 4K signals through a single BNC cable

Connecting to compatible cameras via triax cable, the compact (1.5U) HDCU-3170 supplies power to the camera, performs signal processing and provides an interface with external equipment.

With the addition of option boards and kits, the HDCU-3170 offers support for various interfaces including 3G SDI and IP. The CCU can provide simultaneous outputs of HD, HDR and SDR when used with HDC-3170 series system cameras.

Combined with the HKCU-SFP30 option board, designed for the SMPTE ST 2110 Professional Media Over Managed IP Network suite of standards, the HDCU-3170 CCU supports essential functionalities required for live IP production including tally, intercom and return.

## Features

### **Compact and versatile**

The compact 1.5U Camera Control Unit creates a standardised 19-inch rack system that is ideal for space-limited production areas.

### **IP functionality for live production**

The optional HKCU-SFP30 interface kit adds essential functionality required for IP live production including ST2110 output and return and NMOS IS-04/05 as well as tally, intercom and return over IP.

### **Eight built-in SDI outputs**

The HDCU-3170 is equipped with eight built-in SDI outputs, including four 3G-SDI outputs. For extra production flexibility.

### **High quality long distance signal transmission**

Adding the optional HKCU-SFP30 supports long distance signal transmission up to 10km over single mode fibre, making the CCU ideal for space-limited environments such as OB vehicles.

### **MENU setting from web browser**

The CCU support menu control from web browser. The status monitoring of multiple CCU, setting file import/export and remote firmware update enhance the efficiency and convenience of the operation.

## Specifications

### General

Power requirements	100 V to 240 V AC, 50/60 Hz
Current consumption	4.5 A (max.)
Operating temperature	5 °C to 40 °C (41 °F to 104 °F)
Storage temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Mass	Approx. 8.1 kg (17 lb 14 oz)

### Input/output connectors

CAMERA FIBER	No
CAMERA TRIAX	Triax connector (x1)
INTERCOM/TALLY/IO PORT	D-sub 50-pin connector (x1) INTERCOM (PROD/ENG), 4 W: 0 dBu, RTS: 0 dBu, CC: -14 dBu PGM, 3 systems, 0dBu/-20dBu (for HDC-3100/HDC-3170) TALLY (R, G, Y) FLAG

RCP/CNU	8-pin multi-connector (x1)
TRUNK	12-pin (x1)
LAN-COM	8-pin (x1)
NETWORK TRUNK	8-pin (x1)
SDI I/O 1 to 4	3G/HD/SD SDI I/O BNC (x4) 3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p, 75 $\Omega$ , 2.970 Gbps/2.967 Gbps HD-SDI: SMPTE ST292, 0.8 Vp-p, 75 $\Omega$ , 1.485 Gbps/1.4835 Gbps SD-SDI: SMPTE ST259, 0.8 Vp- p, 75 $\Omega$ , 270Mbps 3G-SDI/HD-SDI/SD-SDI, character signal selectable
REFERENCE IN/OUT	BNC (x2), loop-through output HD: SMPTE ST274, tri-level sync, 0.6 Vp-p, 75 $\Omega$ SD: Black burst (NTSC: 0.286 Vp-p, 75 $\Omega$ /PAL: 0.3 Vp-p, 75 $\Omega$ ) or NTSC 10F-BB

## Input connectors

AC IN	100 V to 240 V AC (x1)
SDI RET 1 to 4	BNC (x4) 3G-SDI: SMPTE ST424/425, 2.970 Gbps/2.967 Gbps HD-SDI: SMPTE ST292, 1.485 Gbps/1.4835 Gbps

SD-SDI: SMPTE ST259, 270 Mbps

PROMPTER 1  
PROMPTER 2/VBS-  
RET

BNC (x2), loop-through output during 1CH mode, terminate internally at 75  $\Omega$  during 2CH mode, analog signal, 1.0 Vp-p, 75  $\Omega$

## Output connectors

AUDIO OUT CH1, CH2

XLR 3-pin, male (x2), 0dBu/-20 dBu/+4 dBu

CHARACTER/ABS/EBU

BNC (x1), VBS, 1 Vp-p, 75  $\Omega$   
HD SYNC: BTA-S001, tri-level sync, 0.6 Vp-p, 75  $\Omega$   
SD SYNC: composite sync, 0.3 Vp-p, 75  $\Omega$   
VBS/HD SYNC/SD SYNC selectable

SDI OUT 1 to 4

3G/HD/SD SDI OUTPUT  
BNC (x4)  
3G-SDI: SMPTE ST424/425 Level-A/B, 0.8 Vp-p, 75  $\Omega$ , 2.970 Gbps/2.967 Gbps  
HD-SDI: SMPTE ST292, 0.8 Vp-p, 75  $\Omega$ , 1.485 Gbps/1.4835 Gbps  
SD-SDI: SMPTE ST259, 0.8 Vp-p, 75  $\Omega$ , 270 Mbps  
3G-SDI/HD-SDI/SD-SDI, character signal selectable

Supplied accessories

Supplied accessories	Number plates (1 set), Before Using this Unit (1), Operating Instructions (CD-ROM) (1)
----------------------	--

Optional accessories

Optional accessories	United States and Canada: Power cord set (1-551-812-XX) Other areas: Power cord set (1-782-929-XX) United States and Canada: Plug holder B (2-990-242-01) Other areas: Plug holder C (3-613-640-01) CCA-5-3 Connection Cable (3 meters), CCA-5-10 Connection Cable (10 meters)
----------------------	--

Related products

			
<b>RCP-3501</b> Remote-control panel for HDC/HSC/HXC series cameras	<b>MSU-3000</b> Master setup unit, multi camera remote control panel for system cameras (horizontal type)	<b>HDC-3100</b> Three 2/3-inch CMOS sensors portable system camera for fibre operation	<b>RCP-3500</b> Remote-control panel for HDC/HSC/HXC series cameras
			
<b>HKCU-</b>	<b>HKCU-</b>	<b>HDVF-EL30</b>	<b>HDVF-EL75</b>

## SM30

Single Mode Fibre  
Extension Kit



## SDI30

12G-SDI Interface  
Kit



OLED 0.7-inch  
colour Full HD  
viewfinder with 3.5-  
inch sub-LCD



7.4-inch OLED  
Viewfinder for  
portable cameras




## HKCU- UHD30

4K HDR Processor  
Board




## HZCU- SNMP50

SNMP Agent license  
for HDCU-5500,  
3500, 3170 and  
HDCU-3100 camera  
control unit




## HZCU- CNFG50

embar+ protocol  
license for HDCU-  
5500, 3500, 3170  
and 3100 camera  
control units



## MSU-3500

Master setup unit,  
multi camera  
remote control  
panel for system  
cameras (vertical  
type)



## HDC-3170

Three 2/3-inch  
CMOS sensors  
portable system  
camera for triax  
operation



## Gallery

