

MKS-R1630

Remote control panel of NS-BUS system



- Overview

The MKS-R series remote panel controls matrix cross points of both IP and SDI routers connected to NS-BUS system.
- Features

Multiple buttons and functionalities

MKS-R1630 has 2 inch display for status indication, showing source, destination and levels, and used for easy configuration of the remote panel. All the panel products support multiple functions such as Salvo, Chop, Protect, Lock, etc. User friendly web menu for configuration.

Redundant network and power supply

Redundant power supply by DC IN and PoE.

Network redundancy supported by two network ports.

Specifications	General	
	Power supply	37V, 57V (PoE), DC IN 12V
	Current consumption	(PoE), 0.7A DC
	Dimensions (W x H	440 x 43.6 x 90 mm (17 3/8 x

x D)	1 3/4 x 3 5/8 in)
Mass	Approx. 1.3kg (2lb 14oz)
Temperature ranges	Operational temperature: +5°C~+40°C (+41°F to +104°F) Storage temperature: -20°C~+60°C (-4°F to +140°F)
LAN	RJ-45 (×2) (PoE x1) 1000BASE-T

Related products



MKS- R3210

Remote control
panel of NS-BUS
system



PWS- 110NM1

IP Live System
Manager
workstation



PWS- 110RS1

Routing Control
Station



MKS- R1620

Remote control
panel of NS-BUS
system

Gallery

