



Extremely versatile, the **CARTONI P90** two-stage pedestal is designed to support camera/lens combination up to 90 Kg, covering the entire range of **STUDIO** and **OB** configurations.

The system is compact and portable, the 2-stage column performs an "on-shot stroke" of 74 cm with a smooth and precise movement.

**The sturdy and yet lightweight dolly** is equipped with high precision double wheels interlocked by a special designed chain allowing accurate travelling and steering, even on shot. Pneumatic bigger wheels are also available as an option.

The **CRAB POSITION** is also available for narrow door ways. All operating devices and control displays are at the cameraman easy access.

The pneumatic column works on simple compressed air which can be loaded with a compressor or a simple hand pump.

The system interfaces with all flat base, 4-bore holes heads or any other bowl based head with an adapter.

Available in "classic black" - Special order only.

## ■ specifications

Maximum pressure: **13.0 atm (187 psi)**

Maximum capacity: **90 Kg (198 lbs)**

Total weight: **60 Kg (132 lbs)**

"on-shot" stroke: **74 cm (29")**

Steering wheel diameter: **57,5 cm (22,6")**

Minimum height: **72 cm (28,4")**

Maximum height: **146 cm (57,5")**

Wheel diameter: **125 cm (49,2")**

Doorway tracking width: **80 cm (31,4")**

Dolly leg radius: **47,5 cm (18,7")**

Column weight: **30 Kg (66 lbs)**

Dolly weight: **30 Kg (66 lbs)**

