		AR.	The Provide States	A Star			
Product	News	Applications Cases	Where to Buy	Support	About us & Contact	Log-in ▶	1


Home > Lighting > Bowens

BL-200 | 200W Bowens Mount COB LED Light



Bowens COB-LED Light

BL-200 is a Bowens mount 200W COB LED light, with DMX control, high CRI/TLCI, accurate color performance, and various Bowens accessories for broadcast studio, mobile studio, live streaming studio applications.





38000Lux @1m Ultra Bright


BL-200 adopts ultra bright 200W COB-LED, 5600K daylight only, provides 38000Lux illuminance at 1 meter distance with standard reflector.


BL-200	1 meter	3 meters	5 meters
Light only	5900Lux	770 Lux	320Lux
With Reflector	38000Lux	4940Lux	2050Lux

Accurate Color Render

CRI 97; TLCI 98

The normal LED light has 80-85 CRI or TLCI, while BL-200 offers the super high CRI at 97 and TLCI at 98, and will not shift the object original colors under light.





Hue

0

000+000

			Sector	Lightness	Chroma	
			R	0	0	
_		1	R/Y	0	0	
			Y	0	0	
			Y/G	0	0	
		a second second	G	0	0	
_			G/C	0	0	
			С	0	0	
			C/B	0	0	
_			в	0	-	
			B/M	0	0	
			M	0	0	
			M/R	0	0	



Separated Control Box


AC & Batteries Power, DMX IN & OUT

BL-200 separates the control box to the light head, to enable power by batteries for outdoor lighting. The control box has PowerCON AC input, 2x V-mount battery plates, DC connector with light head, 5-pin DMX in & out, control buttons and LCD display.

Dual Batteries Installation


BL-200 control box can be fixed to 25-45mm light stand, and quickly released by a V welge structure, which is strong enough for 2x large capacity batteries.





Various Bowens Accessories

BL-200 provides various Bowens mount light shape accessories, including quick setup octagonal softbox, lantern softbox, parabolic dome softbox, and beauty dish, snoot, fresnel lens ect, for optional purchase.




Smart Phone APP Control

IOS and Android

BL-200 and its series model BL-150E, BL-300, can be connected to smart phone by bluetooth, and you can rename and group the lights, adjust dimmer, select light effects, and sync the light effect to a music in your device.

IOS APP: App Store, search "DeSal Lite+" Android APP: Download HERE.



SWIT Electronics Europe GmbH

Heerdterbuschstrasse 10 / HALLE 9, 41460 Neuss, NRW Germany VAT: DE308323924 WEEE-Reg.-Nr. DE 37399843 Email: info@swit-europe.com

Email Newsletter

Please enter Email address below and subscribe our newsletters.

submit

Privacy Policy

leave a message

SWIT®

Bowens Mount COB-LED Lights

BL- series



BL-150E 150W AC Power Only, Built-in Controller





BL-200 200W AC & Battery Power, Separate Controller 300W A

BL-300 300W AC & Battery Power, Separate Controller

	Ultra Brigh 5600K Daylight		EDs	
	, 0	1 meter	3 meters	5 meters
BL-150E	Light only	4400Lux	570 Lux	240Lux
BT-120E	With Reflector	27290Lux	3550Lux	1470Lux
BL-200	Light only	5900Lux	770Lux	320Lux
DL-200	With Reflector	38000Lux	4940Lux	2050Lux
BL-300	Light only	12100Lux	1570Lux	650Lux
	With Reflector	54000Lux	7020Lux	2910Lux
		CI 00		R1
The second s	CRI 97; TLO Accurate Color		R14	R2 R3
		R 0 0	R13 R12 R12 R12 R11 R11 R10	R9 R8
	9x Light Ef With Intensity a	and Speed A	adjustment	



Bowens Mount Accessories Optional Purchase





BA-OCT36 36-inch Easy-open Octagonal Softbox With dual diffusers



BA-LAN26 26-inch Easy-open Lantern Softbox



BA-PARA26 26-inch Easy-open Parabolic Dome Softbox With eggcrate and dual diffusers



BA-BD16 16-inch Beauty Dish with 40° Honeycomb and diffuser



BA-ST3

3.1-inch Snoot with honeycomb with 25° & 30° Honeycombs and 5x color filters



BA-F3X Fresnel 12-40° 3x Lens with 10x color filters

Specifications

Model	BL-150E	BL-200	BL-300	
LED	150W COB-LED	200W COB-LED	300W COB-LED	
Luminance	27290Lux @ 1m with reflector	38000Lux @ 1m with reflector	54000Lux @ 1m with reflector	
Color temp	5600K	5600K	5600K	
Color rendering	CRI 97; TLCI 98	CRI 97; TLCI 98	CRI 97; TLCI 98	
DMX	DMX512 5pin XLR in & out	DMX512 5pin XLR in & out	DMX512 5pin XLR in & out	
Input voltage	AC 100-240V (PowerCON)	AC 100-240V (PowerCON), battery 11-17V	AC 100-240V (PowerCON), battery 11-17V	
Dimension	272×199×333mm	Light: 272×199×333mm Controller: 170×125×218mm	Light: 301×199×333mm Controller: 170×125×218mm	
Weight	2.15kg	Light 1.8kg; Controller 1.9kg	Light 2.5kg; Controller 1.9kg	

SWIT Electronics Co., Ltd. +86-25-85805753 http://www.swit.cc Email: contact@swit.cc SWIT Electronics America, Inc 1-(408)260-8258 http://www.swit.us Email: info@swit.us SWIT Electronics Europe GmbH +49(0)2131 6632331 http://www.switeu.com Email: info@swit-europe.com





Facebook Page

Instagram















