

Home > Battery > Gold Mount

PB-S98A | 98Wh Multi-sockets Square Digital Battery



- › Square shape design for Cine-cameras
- › Max 150W, 12A load
- › 2x D-tap output sockets (120W/10A in total)
- › 1x USB 5V/2A power output sockets
- › OLED display accurate remaining run time
- › Multiple circuit protections



MSRP Ex TAX / Shipping

Features Specifications Download What's in box Optional accessory Related



Square Shape Design

PB-S series camera batteries are compact designed, shorter than normal V/Gold mount batteries, and match perfectly with most of the Cine-cameras.



98Wh Capacity, 150W/12A load

Consists of 12pcs of high class 18650 battery cells, nominal voltage is 14.4V and reaches 98Wh / 6.8Ah high capacity. Can run approx 3 hours for normal ENG cameras. Provides at least 150W/12A high load even at 1% capacity.

2x D-tap, 1x USB

PB-S98A provides 2x D-tap output sockets with 10A/120W load, and 1x USB 5V/2A socket, to power other on-camera devices together.



Digital Power Info

OLED display accurate remaining run time

The build-in OLED can displays remaining power percentage, remaining working time, low power warning, and battery cycle times.



Display power percentage when the battery is free or during charging. Lightning icon is displayed during charging.



Display remaining running time when the battery is powering on camera or any devices. Press power check button can switch to power percentage display.



If the working time is less than ten hours, it will display 0-9:59; If the working time is more than 10 hours, it will display remaining working hours.



Long press power check button for 5 seconds, it will display battery cycle times.

Battery Protection Display

When any over load, over charging, short circuit, high/low temperature detected, the battery will protect itself and display protection information. You can take steps to re-active battery, to ensure the best battery condition and prolong battery life.



Over temperature protection, please remove the battery and place at room temperature to recover.



Low temperature protection, please remove the battery and place at room temperature to recover.



1. Over charging protection
2. Over load protection
3. Short circuit protection
Please remove the battery, check pin status, and the battery will recover automatically after 30 seconds.



E01/E02/E03: Not recoverable error, please contact manufacturers to repair, do not disassemble the battery by yourselves.

SWIT Electronics Europe GmbH

Heerdterbuschstrasse 10 / HALLE 9,
41460 Neuss, NRW Germany
VAT: DE308323924
WEEE-Reg.-Nr. DE 37399843
Email: info@swit-europe.com

Email Newsletter

Please enter Email address below and subscribe our newsletters.

[Privacy Policy](#)

[leave a message](#)

Multi-sockets Square Li-ion Battery

PB-S series camera batteries are compact designed, shorter than normal V/Gold mount batteries, and match perfectly with most of the Cine-cameras.

The build-in OLED can display accurate power info during charging and discharging, and support viewfinder info display on both SONY and RED cameras.

To make convenient connections, the PB-S batteries provide USB output socket and up to 4 D-tap sockets for camera-top devices.



PB-S98A/S 98Wh

- ◆ Square shape design for Cine-cameras
- ◆ Max 150W, 12A high load
- ◆ 2× D-tap output sockets
- ◆ 1× USB 5V/2A power output sockets
- ◆ OLED display accurate remaining run time
- ◆ Display power info in both SONY & RED
- ◆ Multiple circuit protections

PB-S98A: Gold mount

PB-S98S: V-mount

Model	PB-S98S	PB-S98A
Battery plate	V-mount	Gold-mount
Nominal voltage	14.4V	14.4V
Capacity	98Wh,6.8Ah	98Wh,6.8Ah
Max output	Electrodes	150W,12A
	D-TAP	120W,10A
	USB	10W,5V/2A
	In total	150W
Dimension	121×95×59mm	121×95×62mm
Net weight	0.809kg	0.800kg
Max charging current	3A	3A
D-TAP socket number	2	2
USB socket number	1	1



Power info display – The OLED displays remaining power percentage, remaining working time, low power warning, and battery cycle times.



Display power percentage when the battery is free or during charging. Lightning icon is displayed during charging.



Display remaining running time when the battery is powering on camera or any devices. Press power check button can switch to power percentage display.



If the working time is less than ten hours, it will display 0~9:59; If the working time is more than 10 hours, it will display remaining working hours.



Long press power check button for 5 seconds, it will display battery cycle times.



SWIT[®]

PB-S98A

14.4V, 98Wh / 6.8Ah

Li-ion Battery Pack

98

INFO 150W/12A
POWER HIGH LOAD

CE UK
CA

SWIT Electronics Co., Ltd.
MADE IN CHINA



SWIT[®]

PB-S98A

14.4V, 98Wh / 6.8Ah

Li-ion Battery Pack

98

INFO 150W/12A HIGH LOAD
CE UK CA

SWIT Electronics Co., Ltd.
MADE IN CHINA

MAX 8A

MAX 8A

MAX 8A

MAX 8A



SWIT[®]

100%

PB-S98A

14.4V, 98Wh / 6.8Ah

Li-ion Battery Pack

98

INFO POWER 150W/12A HIGH LOAD CE UK CA

SWIT Electronics Co., Ltd.
MADE IN CHINA