

Home > Charger/Adaptor > V-mount

PC-P430S | 4-ch V-mount Fast Charger

- > V-mount battery charger
- > 4-ch simultaneous charging
- > 3A per channel quick charging
- > 2x 15V/6A 4-pin XLR DC output
- > LED charging indicators for each channel



 MSRP Ex TAX / Shipping

[Features](#) [Specifications](#) [Download](#) [What's in box](#) [Optional accessory](#) [Related](#)

4-ch Simultaneous Quick Charger

For V-mount batteries

PC-P430S can charge 4pcs V-mount camera batteries simultaneously. The charging output is DC16.8V, 3A each channel.



LED Charging Indicators

The PC-P430S has LED charging indicators on the front panel, indicates the real time capacity of each channel by different colors:
 Display Red: Battery is charging, capacity below 80%;
 Display Yellow: Battery is charging, capacity above 80%;
 Display Green: Charging finished.

AC-DC Adapting Output

PC-P430S has 2x 4-pin XLR female connector on the front panel. Connected with SWIT S-7102 XLR female to male cable (optional purchase), the PC-P430S can be used as AC-DC adaptor of 2-ch DC 15V, 6A, 90W simultaneous output.
 *Please note the AC-DC adapting output will not work when battery is charging.



SWIT Electronics Europe GmbH

Heerdterbuschstrasse 10 / HALLE 9,
 41460 Neuss, NRW Germany
 VAT: DE308323924
 WEEE-Reg.-Nr. DE 37399843
 Email: info@swit-europe.com

Email Newsletter

Please enter Email address below and subscribe our newsletters.

[Privacy Policy](#)

[leave a message](#)



SWIT 4-ch V-mount Battery Charger
PC-P430S

CH-1 CH-2 CH-3 CH-4

DC OUT 1 DC OUT 2

视威
SWIT
S-8002S
14.4V 1300mAh V-MOUNT
CE

SWIT S-8002S
14.4V 1300mAh
CE



SWIT[®]

4-ch V-mount Battery Charger

PC-P430S

CH-1



100%

0%


CH-3

CH-2

CH-4



DC OUT 1



DC OUT 2



SWIT

4-ch V-mount Battery Charger
PC-P430S

CH-1

CH-2

CH-3

CH-4



DC OUT 1

DC OUT 2



SWIT®


4-ch V-mount Battery Charger
PC-P430S

CH-1



100%


CH-2




0%

CH-3

CH-4



DC OUT 1



DC OUT 2

