

Home > Charger/Adaptor > V-mount

S-3822S | 2-ch V-mount Fast Charger



- > Charging V-mount batteries
- > 2-ch simultaneous charging
- > 3A charging current per channel
- > LED charging indicators
- > Support AC to 4-pin XLR output
- > Light weight and portable



MSRP Ex TAX / Shipping

[Features](#) [Specifications](#) [Download](#) [What's in box](#) [Optional accessory](#) [Related](#)

2-ch Simultaneous Charger

Charging current: 3A per channel

The portable charger S-3822S can charge 2 V-mount batteries simulta- neously. The charging output is DC 16.8V, 3A×2



LED Charging Indicators

S-3822S has LED charging indicators on the front panel, indicates the real time capacity of each channel by different colors:

- Display Red: Battery is charging, capacity below 80%;
- Display Yellow: Battery is charging, capacity above 80%;
- Display Green: Charging finished.

AC-DC Adapting Output

S-3822S has a 4-pin XLR female connector on the front panel. Connected with SWIT S-7102 XLR female to male cable (optional purchase), the S-3822S can be used as AC-DC adaptor of DC 15V, 6A, 90W output. Please note the AC-DC adapting output will not work when battery is charging.



SWIT Electronics Europe GmbH

Heerdterbuschstrasse 10 / HALLE 9,
41460 Neuss, NRW Germany
VAT: DE308323924
WEEE-Reg.-Nr. DE 37399843
Email: info@swit-europe.com

Email Newsletter

Please enter Email address below and subscribe our newsletters.

[Privacy Policy](#)

[leave a message](#)



SEARCH

[Field LCD Monitor](#)

[Rack-Mount Monitor](#)

[Studio Monitor](#)

[Power Station Box](#)

[V-Mount Battery](#)

[Gold-Mount Battery](#)

[NP-1 Style Battery](#)

[Charger / Adaptor](#)

[Converter/Distributo](#)

[Fiber Camera System](#)

[Wireless Transmission System](#)

[LED Light](#)

[Battery for Sony](#)

[Battery for Panasonic](#)

[Battery for Canon](#)

[Battery for JVC](#)

[Accessories](#)

[Gra-Vue Products](#)

[AVIPAS Products](#)

[B-Stock & Clearance](#)

[Dealers/ Rentals](#)

[Sales Reps](#)

[Shipping & Returns](#)

[Material Safety Data Sheets](#)

[FAQ](#)

[Home](#) > [Charger / Adaptor](#) > S-3822S 2-ch V-Mount Battery Charger

S-3822S 2-ch V-Mount Battery Charger



Item# S-3822S

\$350.00

Availability: Usually ships in 2-3 weeks

Product Description



The portable charger S-3822S can charge 2 V-mount batteries simultaneously. The charging output is DC 16.8V, 3A².

Key Features:

- V-mount battery charger
- 2-ch simultaneous charging
- 3A charging current per channel
- LED charging indicators
- Support AC to 4-pin XLR output
- Light weight and portable

Specifications:

Input	AC 100V-240V 50/60Hz
Power consumption	Max 136W
Charging output	DC 16.8V, 3Ax2-ch
Adapting output	DC 14.4V, 5A
Working temperature	0 ² C ~ +40 ² C
Working humidity	10% ~ 90%
Dimension	228 ² 140 ² 120mm
Weight	Approx. 1.0kg

LED Charging Indicators

S-3822S has LED charging indicators on the front panel, indicates the real time capacity of each channel by different colors:

Display Red: Battery is charging, capacity below 80%

Display Yellow: Battery is charging, capacity above 80%

Display Green: Charging finished



AC-DC Adapting Output

S-3822S has a 4-pin XLR female connector on the front panel. Connected with SWIT S-7102 XLR female to male cable (optional purchase), the S-3822S can be used as AC-DC adaptor of DC 14.4V, 5A, 72W output.

Please note the AC-DC adapting output will not work when battery is charging.



Warranty Period: two years conditional.

Related Items and User Manual:

[SWIT S-7102 4-pin XLR Cable](#)

[View S-3822S V-mount Charger User Manual](#)



S-3822A/S

2-ch Simultaneous Battery Charger & Adaptor



S-3822A
for Gold Mount



S-3822S
for V-Mount

Features


- ◆ Portable battery charger
- ◆ 2-ch simultaneous charging
- ◆ 3A charging current per channel
- ◆ LED charging indicators
- ◆ Support AC to 4-pin XLR output

Specifications:

Input	100~240VA, 50/60Hz
Power	136W(Max)
Charging Output	DC 16.8V, 3A(Max)×2
Adapting Output	DC 15V, 6A(Max)
Working Temperature	0°C ~ +40°C
Working Humidity	10%~90%
Dimension	228mm×140mm×86mm(S-3822A) 228mm×140mm×120mm(S-3822S)
Weight	Appx 1.0kg



Can charge 2x **V-mount / Gold mount** batteries simultaneously. The charging output is DC **16.8V, 3Ax2**



LED indicates the charging status for each channel:
Red: on charging, < 80%;
Yellow: on charging, ≥80%;
Green: charging finished.



AC-DC adapting output via 4-pin XLR female connector. Offer DC **15V, 6A, 90W** output. (will not output when battery is charging)




SWIT Electronics Co., Ltd.
Website: www.swit.cc
Email: contact@swit.cc
Tel: +86 2585805753
Fax: +86 2585805296

Distributed by:

L

R





SWIT[®]

MODEL:
S-3822S

DUAL CHANNEL

L R



DC OUT
Max 90W
15V, 6A



Remove batteries
to enable DC out

SWIT[®]

S-8113S
14.4V 160Wh/11.1Ah
Li-Ion Battery

High Load Fast Charge

SWIT ELECTRONICS CO., LTD.
www.swit.cc



SWIT®

MODEL:

S-3822S

DUAL CHANNEL

L

R

100%

0%

DC OUT

Max 90W
15V, 6A

Remove batteries
to enable DC out

DC OUT

Max 72W
14.4V, 5A



Remove batteries
to enable DC out