

Home > Charger/Adaptor > V-mount

TD-R230S | 48V 750W Light Stand Power Adaptor



- > Install 2x 28.8V V-mount batteries
- > Support SWIT HB-C420S batteries
- > Support SWIT PB-H290S batteries
- > Neutrik 3-pin XLR Regulated 48V, 750W output
- > Neutrik SpeakON 22-33.6V, 750W output
- > Power indicators for each battery
- > 25-45mm light stand install



MSRP Ex TAX / Shipping

Features Specifications Download What's in box Optional accessory Related

Cine Lights Portable Power

TD-R230S light stand power adaptor is particularly to power the high draw cine lights up to 750W, by only 2x V-mount batteries hooked on light stand, portable and convenient for moving the light fixtures on set.



48V 750W High Output

100% Power Vortex 8, Skypanel, Orbitor etc

TD-R230S supports 2 of 28.8V V-mount batteries install, and by SWIT HB-C420S batteries, the TD-R230S adaptor could output 48V 750W and 22-33.6V 750W high power for cine lights like Creamsources Vortex 8, ARRI Skypanel S60/S120, ARRI Orbitor, Aputure Nova P600C, etc.

Run Time Chart By 2x HB-C420S batteries

Brand	Light fixture	Max Power	DC-IN socket	Power Solution	Run Time
ARRI	Orbitor	430W	48-52V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours
ARRI	Skypanel S60/120	430W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours
ARRI	L5-C	150W	23-36V, 4-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>5.6 hours
Aputure	Nova P300C	360W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.3 hours
Aputure	Nova P600C	720W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Aputure	LS600X/D/C	720W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Creamsource	Vortex 4	325W	48V, Ecomate	TD-R230S (3-pin) + 2x HB-C420S	>1.3 hours
Creamsource	Vortex 8	650W	48V, Ecomate	TD-R230S (3-pin) + 2x HB-C420S	>2.6 hours
Fiilex	Q8 / Matrix Color	300W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.8 hours
Kino Flo	Freestyle T44/T24	150W	18-36V, 3-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>5.6 hours
Lightstar	LUXED 4	720W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
NANLITE	Forza 500	500W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>2.8 hours
NANLUX	Dyno 650C	650W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>1.3 hours
Prolights	EclPanel TWCJR	220W	24-36V, 4-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>3.8 hours
Prolycht	Orion 675 FS	675W	46-50V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Velvet	KOSMOS	400W	26-48V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours

DC Output Sockets

TD-R230S provides 3-pin XLR regulated 48V DC output of 750W load, and Neutrik SpeakON 22-33.6V DC output of 750W load. The system draws 2 batteries one-by-one or simultaneously according to the real time power load. The top indicators display the discharging status of each battery.



Easy Install on Light Stands

TD-R230S has extremely compact size without fans, and fits on 25mm-45mm diameter light stand. It's balanced with 2 batteries and reliable locker.



SWIT Electronics Europe GmbH

Heerdterbuschstrasse 10 / HALLE 9,
41460 Neuss, NRW Germany
VAT: DE308323924
WEEE-Reg.-Nr. DE 37399843
Email: info@swit-europe.com

Email Newsletter

Please enter Email address below and subscribe our newsletters.

[Privacy Policy](#)

[leave a message](#)

SWIT

TD-R230S

light stand power adaptor

Dual Batteries Adaptor

Install 2x 28.8V V-mount batteries

Neutrik SpeakON 22-33.6V 750W output

3-pin XLR Reg. 48V 750W output



■ Run Time Chart By 2x HB-C420S batteries

Light fixture	Power	DC-IN	Power Solution	Run Time
ARRI Orbitor	430W	48-52V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours
ARRI Skypanel S60/120	430W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours
ARRI L5-C	150W	23-36V, 4-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>5.6 hours
Aputure Nova P300C	360W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.3 hours
Aputure Nova P600C	720W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Aputure LS600X/D/C	720W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Creamsource Vortex 4	325W	48V, Ecomate	TD-R230S (3-pin) + 2x HB-C420S	>1.3 hours
Creamsource Vortex 8	650W	48V, Ecomate	TD-R230S (3-pin) + 2x HB-C420S	>2.6 hours
Fiilex Q8 / Matrix Color	300W	48, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.8 hours
Kino Flo T44/T24	150W	18-36V, 3-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>5.6 hours
Lightstar LUXED 4	720W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
NANLITE Forza 500	500W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>2.8 hours
NANLUX Dyno 650C	650W	48V, SpeakON	TD-R230S (3-pin) + 2x HB-C420S	>1.3 hours
Prolights EclPanel TWCJR	220W	24-36V, 4-pin XLR	TD-R230S (SpeakON) + 2x HB-C420S	>3.8 hours
Prolycht Orion 675 FS	675W	46-50V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>1.2 hours
Velvet KOSMOS	400W	26-48V, 3-pin XLR	TD-R230S (3-pin) + 2x HB-C420S	>2.1 hours


SWIT Electronics Co., Ltd.
+86-25-85805753
<http://www.swit.cc>
Email: contact@swit.cc

SWIT Electronics America, Inc
1-(408)260-8258
<http://www.switusa.com>
Email: info@swit.us

SWIT Electronics Europe GmbH
+49(0)2131 6632331
<http://www.switeu.com>
Email: info@swit-europe.com



Facebook Page



Instagram



LinkedIn







